

ALR 37/56 mm

GBK 50W 12V R56 25D FR 1CT

Delivers high lumen output and excellent color rendering for precise accent and display lighting. Philips Halogen Aluminum Reflector Lamps provide continuous color and high luminous intensity for precise accent and display lighting. These lamps offer a rated average life ranging from 2000 hours and feature excellent beam qualities for accent or ambient lighting.

[See full family](#)

Add to ProjectPlanner



Images



Diagrams

[Print this page](#) [Contact us](#) [SHARE](#) [f](#) [t](#) [e](#) ...

Product Information

General Characteristics

Philips Code	6439/FR	•
ANSI Code Halogen	GBK	•
Base	Single Contact • Bayonet [Single Contact Bayonet]	
Base Information	na	•
Bulb	R56 [R 56mm]	•
Bulb Finish	Frosted	•
Operating Position	Universal [Any or Universal (U)]	
RatedAvgLife(See Family Notes)	2000 hr	•

Light Technical Characteristics

Beam Angle	25 D	•
Beam Angle Technical	25 D	•
Approx. MBCP	2000 (max) cd	•
Color Rendering Index	100 Ra8	•
Color Temperature	3000 K	•
Color Temperature technical	3000 K	•

Electrical Characteristics

Watts	50 W	•
Lamp Wattage Technical	50.0 W	•
Voltage	12 V	•
Lamp Current	4.17 A	•
Dimmable	Yes	•

Luminaire Design Requirements

Cap-Base Temperature	350 (max) C	•
Bulb Temperature	250 (max) C	•

Product Dimensions




Overall Length C	60 (max) mm	•
Diameter D	58 (max) mm	•

Product Data

Product number	340919	•
Full product name	Error EOC	•

[+ More info / Hide info](#)


Downloads

-  [Leaflet](#)
217.43 KB
-  [Product Images](#)
-  [Product Diagrams](#)

Installation diagrams




B15 R56
[+ Zoom](#)



any
[+ Zoom](#)


Photometrics



Aluline 37/56
50W 25D
[+ Zoom](#)



Aluline 37/56
50W 25D
[+ Zoom](#)



Aluline 37/56
50W 25D
[+ Zoom](#)