



Product Number: 54836

Order Abbreviation: BHC/DYS/DYV

General Description: 600 watt, tungsten halogen, medium to high voltage, single-ended

| Product Information | |
|-----------------------------------|--------------------------------------|
| Abbrev. With Packaging Info. | BHCDYSDYV 120V 24/CS 1/SKU |
| ANSI Code | BHC/DYS/DYV |
| Application | Projector, Microfilm, Stage & Studio |
| Average Rated Life (hr) | 75 |
| Base | GZ9.5 Bipin Prefocus |
| Bulb | T6 |
| Class | C (gas) |
| Color Rendering Index (CRI) | 100 |
| Color Temperature (K) | 3200 |
| Diameter d (in) | 0.787 |
| Diameter d (mm) | 20.00 |
| Distance a (in) | 1.424 |
| Distance a (mm) | 36.5 |
| Filament | CC-6 |
| Filament Dimensions Length (in) | 0.187 |
| Filament Dimensions Length (mm) | 4.8 |
| Filament Dimensions Width (in) | 0.441 |
| Filament Dimensions Width (mm) | 11.3 |
| Lamp Finish | Clear |
| Length l (in) | 2.496 |
| Length l (mm) | 64 |
| Length l max. (in) | 2.496 |
| Length l max. (mm) | 64 |
| LIF Code | A1/264 |
| Light Center Length - LCL (in) | 1.424 |
| Light Center Length - LCL (mm) | 36.5 |
| Luminous Flux (lm) | 17500 |
| Maximum Overall Length - MOL (in) | 2.496 |
| Maximum Overall Length - MOL (mm) | 64 |
| Nominal Voltage (V) | 120.00 |
| Nominal Wattage (W) | 600.00 |
| Operating Position | s 90 |
| Type of Current | AC |

Footnotes

- s (Operating Position) = Vertical, base down