Product Details Page 1 of 1



Product 56210 **Number:**

Order 500PAR56Q/HAL/NSP 120V

Abbreviation:

General Tungsten Halogen PAR56 Mogul End Prong 500Watt

Description: 120Volt Very Narrow Spot Beam

Product Information	
Abbrev. With Packaging Info.	500PAR56QNSP 120V 12/CS 1/SKU
Approx. Lumens	8800
Average Rated Life (hr)	4000
Base	External Mogul End Prong GX16D
Beam Angle (deg)	15
Beam Type	NSP
Bulb	PAR56
Centerbeam Candlepower (cp)	78500
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	2950
Diameter (in)	7.000
Diameter (mm)	177.80
Ecologic	YES
Family Brand Name	Large PAR
Filament	CC-6
Lamp Finish	Reflector
Maximum Overall Length - MOL (in)	5.000
Maximum Overall Length - MOL (mm)	127
Nominal Voltage (V)	120.00
Nominal Wattage (W)	500.00



Footnotes

- Should be shielded against moisture falling on bulb.
- A suitable protective shield, screening technique, or both must be used to protect people and surroundings from the possibility of a lamp shattering and from possible ultraviolet radiation.
- r use only with heat-resisting connector and with bulb supported by bulb rim or metal shell of base.