



HIGH WATTAGE SPIRAL

High Wattage Spiral CFL								
Nominal Wattage	Overdrive Model #	Item Description & CCT	Initial Lumen	Average Rated Life (Hrs.)	Diameter (Inches/mm)	Length/ (Inches/mm)	Pack Master	Item #
36	36W/ODSP	36W Spiral T4- CFL-Soft White	2400	10000	2.6 / 67	7.0 / 178	12	107
36	36W/ODSP/41K	36W Spiral T4- CFL-Cool White	2400	10000	2.6 / 67	7.0 / 178	12	207
36	36W/ODSP/50K	36W Spiral T4- CFL-Natural DL	2400	10000	2.6 / 67	7.0 / 178	12	132
• 40	40W/ODSP	40W Spiral T4- CFL-Soft White	2600	10000	2.6 / 67	7.3 / 185	12	133
40	40W/ODSP/41K	40W Spiral T4- CFL-Cool White	2600	10000	2.6 / 67	7.3 / 185	12	208
40	40W/ODSP/50K	40W Spiral T4- CFL-Natural DL	2700	10000	2.6 / 67	7.3 / 185	12	134
55	55W/ODS	55W Spiral T5- CFL-Soft White	2600	10000	3.1 / 80	9.6 / 245	12	040
55	55W/ODS/41K	55W Spiral T5- CFL-Cool White	3600	10000	3.1 / 80	9.6 / 245	12	209
55	55W/ODS/50K	55W Spiral T5- CFL-Natural DL	3600	10000	3.1 / 80	9.6 / 245	12	103
85	85W/ODSP	85W Spiral T5- CFL-Soft White	5800	10000	4.1 / 102	10.0 / 254	12	166
85	85W/ODSP/41K	85W Spiral T5- CFL-Cool White	5800	10000	4.1 / 102	10.0 / 254	12	205
85	85W/ODSP/50K	85W Spiral T5- CFL-Natural DL	5800	10000	4.1 / 102	10.0 / 254	12	167
105	105W/ODSP	105W Spiral T5- CFL-Soft White	7150	10000	4.1 / 102	10.7 / 272	12	168
105	105W/ODSP/41K	105W Spiral T5- CFL-Cool White	7150	10000	4.1 / 102	10.7 / 272	12	206
105	105W/ODSP/50K	105W Spiral T5- CFL-Natural DL	7150	10000	4.1 / 102	10.7 / 272	12	169
105	105W/ODSP/E39/50K	105W Spiral T5- CFL-Natural DL-Mogul Base	7150	10000	4.1 / 102	11.2 / 280	12	170
150	150W/ODSP/E39/50K	150W Spiral T6- CFL-Natural DL-Mogul Base	8800	10000	4.7 / 120	13.0 / 331	6	245
180	180W/ODSP/E39/50K	180W Spiral T6- CFL-Natural DL-Mogul Base	11100	10000	4.7 / 120	14.3 / 364	6	246

Excellent Scotopic lumens compared to all HID lamps which further enhances the effective perceived light from High Wattage Spiral CFL due to high CRI

Applications



PENDANT FIXTURES



RECESSED CANS



OUTDOOR COVERED



WALL SCONCE



CEILING

Features

- 10,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Spiral shape for improved Lumen/Watt
- Replaces low wattage HID bulbs

Notes

- Not Dimmable
- Available in other color temperature also (upon request)
- Dimension with + 0.1 inch tolerance

