

LED-FL-10-12v

LED-FL-10-120v

LED- FL-20-12v

LED-FL-20-120v

LED-FL-30-12v

LED-FL-30-120v

Specify Housing / Kelvin Color

10w Size: 4.5w x 3.5h

10w Lumens: 820 avg.

10w Spread: 20 ft x 20 ft

10w Compare to: 50w

20w Size: 7"w x 5.5"h

20 Lumens: 1650 avg.

20w Spread: 30 ft x 30 ft

20w Compare to: 100w

30w Size: 8.5"w x 7.5"h

30 Lumens: 2350 avg.

30w Spread: 40 ft x 40 ft

30w Compare to: 150w

Material: Powder coated cast aluminum w/ stainless screws.

Std. Finish: Bronze

Optional Finish: Black, Gray, White

Std. Kelvin: 3000k

Optional Kelvin: 4100k or 5,000k

12V Voltage Range: 10v-20v AC

120V Voltage Range: 100v- 277v AC

Wire: 3 ft. 18-2 SJ Cord

Beam Angle: 120 degree (super flood)

12v Mounting: ½" npt w/ stake

120v Mounting: Self bracket

Rating: 50,000 hour

Option: Glare shield visor

12v and 100/277v LED Power Stars

LED Power Star floods are ideal for large trees, walls and building facades. Works off conventional AC power and UL listed.

Ground or Wall Mount with optional cut off visor.

One fixture can replace up to 2-3 fixtures.

Five - Seven times more efficient than conventional lighting (approx.) and rated at 50,000 hours.



Optional Cut - Off Glare Visor Available