



PROMOLUX PLATINUM T12 LAMPS REGULAR UNCOATED



Lamp Type	Part Number	Lamp Watts	Nominal Length		Diameter		Contact Pins	Avg Life Hrs	Box Qty
			(mm)	(in)	(mm)	(in)			
F20 T12	11020	20	600	24	38	1 1/2	MBP	10,000	12
F30 T12	11030	30	900	36	38	1 1/2	MBP	20,000	12
F40 T12	11040	40	1200	48	38	1 1/2	MBP	20,000	25
F48 T12 SL	11048	40	1150	46	38	1 1/2	SP	10,000	12
F60 T12 SL	11060-4*	50	1500	60	38	1 1/2	SP	12,000	4
F72 T12 SL	11072-4	55	1800	72	38	1 1/2	SP	12,000	4
F96 T12 SL	11096-4	75	2400	96	38	1 1/2	SP	18,000	4
F48 T12 HO	11148	60	1150	46	38	1 1/2	RDC	10,000	12
F60 T12 HO	11160*	75	1500	60	38	1 1/2	RDC	12,000	12
F72 T12 HO	11172-4	85	1800	72	38	1 1/2	RDC	12,000	4
F96 T12 HO	11196-4	110	2400	96	38	1 1/2	RDC	12,000	4

PROMOLUX PLATINUM T12 Lamps are most commonly found as overhead lighting in meat departments and in older display cases. In addition, older low temp (freezer) cases were typically installed with high output (HO) lamps).

*While quantities last; box sizes may vary.