


Project:	Toshiba Lamp:
Type:	Notes:

Ordering Information

Ordering Code	Input Voltage (VAC)	Lamp Shape	Base Type	Wattage (W)	CCT ¹	Initial Lumens (lm) ²	Lamp Efficacy (lm/W)	Rated Life (hrs) ³	CRI	Power Factor	Equivalency ⁴	Lamp Weight lb (g)	Bulb Finish	
4B11/27CF-UP	120	B11	E12	3.8	2700K	185	48.7	25,000	82	0.63	25W Incandescent	0.10 (45)	Frost	●
4B11/27CC-UP	120	B11	E12	3.8	2700K	175	46.1	25,000	82	0.63	25W Incandescent	0.10 (45)	Clear	●

- CCT Range complies to ANSI C78.377-2008.
- Thermally stable typical lumens ($\pm 10\%$).
- Rated life is based on 70% lumen maintenance and engineering testing and probability analysis.
- Equivalency based on the ENERGY STAR[®] Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: All information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility. All lamps meet ENERGY STAR Integral LED Lamp requirements and will be submitted for testing.



Dimensions

Model Candelabra
MOL (A) 4.26" (108.2 mm)
Diameter (B) 1.37" (34.8 mm)



Note: Lamp shape conforms to ANSI C78.21-2003. Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Ordering Code	40W Halogen
4B11/27CF-UP	\$38.87
4B11/27CC-UP	\$38.87

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.

Ordering Guide

4	B11	/	27	C	C/F	UP
Wattage	Lamp Type		CCT	Lumens	Bulb Finish	Packaging
3.8 Watts = 4	B11 = B11		2700K = 27	185 Lumens = C 175 Lumens = F	Clear = C Frosted = F	US Professional Package = UP