



ProLume® Plug-Ins

Halco
LIGHTING TECHNOLOGIES

Halco's ProLume Plug-In CFLs are an energy efficient, long-life alternative to Incandescent lamps. They are available in Single and Double Tube 2-Pin; Single, Double, Triple and Spiral Tube 4-Pin; Flat Quad 4-Pin and High Lumen 4-Pin PLL. All Halco Plug-In CFLs use a tri-phosphor coating, which produces high CRI. These long life lamps are available in wattages from 5W to 57W with color temperatures ranging from 2700K to 5000K.

Specifications:

- Save up to 80% in energy costs compared to standard incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI
- Lead-free glass
- End-of-Life protection
- 2700, 3500, 4100 and 5000K
- 10,000 + Hours Average Rated Life
- Low maintenance
- TCLP compliant
- 1-Year Limited Warranty

Markets:

- Residential
- Commercial

Applications:

- Wall sconces
- Down lighting
- Task lighting
- Security

- » TCLP Compliant
- » End-of-Life Protection
- » 1-Year Limited Warranty

where there's light, there's
halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com

Ordering Information

COMPACTS

Watt	Base	Product #	Product Code	Description	Pkg. Qty.	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg Rated Life	MOL (inc)
Single Tube 2-Pin											
T4											
5 WATT	G23	109100	PL5S/27/ECO	Warm White	1/50	2700	82	250	210	12000	4.25"
5 WATT	G23	109102	PL5S/41/ECO	Cool White	1/50	4100	82	250	210	12000	4.25"
7 WATT	G23	109106	PL7S/27/ECO	Warm White	1/50	2700	82	400	335	12000	5.43"
7 WATT	G23	109107	PL7S/35/ECO	White	1/50	3500	82	400	335	12000	5.43"
7 WATT	G23	109108	PL7S/41/ECO	Cool White	1/50	4100	82	400	335	12000	5.43"
9 WATT	G23	109112	PL9S/27/ECO	Warm White	1/50	2700	82	600	505	12000	6.61"
9 WATT	G23	109144	PL9S/35/ECO	White	1/50	3500	82	600	505	12000	6.61"
9 WATT	G23	109116	PL9S/41/ECO	Cool White	1/50	4100	82	600	505	12000	6.61"
9 WATT	G23	109118	PL9S/50/ECO	Natural White	1/50	5000	82	600	505	12000	6.61"
13 WATT	GX23	109126	PL13S/27/ECO	Warm White	1/50	2700	82	825	695	12000	7.20"
13 WATT	GX23	109128	PL13S/35/ECO	White	1/50	3500	82	825	695	12000	7.20"
13 WATT	GX23	109130	PL13S/41/ECO	Cool White	1/50	4100	82	825	695	12000	7.20"
13 WATT	GX23	109132	PL13S/50/ECO	Natural White	1/50	5000	82	825	695	12000	7.20"
Single Tube 4-Pin Electronic											
T4											
13 WATT	2GX7	109134	PL13S/E/27/ECO	Warm White EOL	1/50	2700	82	825	695	12000	6.30"
13 WATT	2GX7	109136	PL13S/E/35/ECO	White EOL	1/50	3500	82	825	695	12000	6.30"
13 WATT	2GX7	109138	PL13S/E/41/ECO	Cool White EOL	1/50	4100	82	825	695	12000	6.30"
13 WATT	2GX7	109140	PL13S/E/50/ECO	Natural White EOL	1/50	5000	82	825	695	12000	6.30"
Double Tube 2-Pin											
T4											
9 WATT	G23-2	109110	PL9D/27/ECO	Warm White	1/50	2700	82	525	440	12000	4.25"
9 WATT	G23-2	109120	PL9D/41/ECO	Cool White	1/50	4100	82	525	440	12000	4.25"
13 WATT	GX23-2	109146	PL13D/27/ECO	Warm White	1/50	2700	82	900	755	12000	4.65"
13 WATT	GX23-2	109148	PL13D/35/ECO	White	1/50	3500	82	900	755	12000	4.65"
13 WATT	GX23-2	109150	PL13D/41/ECO	Cool White	1/50	4100	82	900	755	12000	4.65"
13 WATT	GX23-2	109149	PL13D/50/ECO	Natural White	1/50	5000	82	900	755	12000	4.65"
18 WATT	G24d-2	109152	PL18D/27/ECO	Warm White	1/50	2700	82	1200	1010	12000	6.02"
18 WATT	G24d-2	109154	PL18D/35/ECO	White	1/50	3500	82	1200	1010	12000	6.02"
18 WATT	G24d-2	109156	PL18D/41/ECO	Cool White	1/50	4100	82	1200	1010	12000	6.02"
18 WATT	G24d-2	109159	PL18D/50/ECO	Natural White	1/50	5000	82	1200	1010	12000	6.02"
T5											
22 WATT	GX32d-2	109862	PL22D/28	Warm White 15 mm Cluster	1/50	2800	82	1200	1010	10000	6.10"
22 WATT	GX32d-2	109864	PL22D/50	Natural White 15 mm Cluster	1/50	5000	82	1200	1010	10000	6.10"
T4											
26 WATT	G24d-3	109158	PL26D/27/ECO	Warm White	1/50	2700	82	1800	1515	12000	6.77"
26 WATT	G24d-3	109160	PL26D/35/ECO	White	1/50	3500	82	1800	1515	12000	6.77"
26 WATT	G24d-3	109162	PL26D/41/ECO	Cool White	1/50	4100	82	1800	1515	12000	6.77"
26 WATT	G24d-3	109163	PL26D/50/ECO	Natural White	1/50	5000	82	1800	1515	12000	6.77"
T5											
28 WATT	GX32d-3	109870	PL28D/28	Warm White 15 mm Cluster	1/50	2800	82	1800	1515	10000	6.70"
28 WATT	GX32d-3	109868	PL28D/50	Natural White 15 mm Cluster	1/50	5000	82	1800	1515	10000	6.70"
Double Tube 4-Pin Electronic											
T4											
13 WATT	G24q-1	109037	PL13D/E/27/ECO	Warm White EOL	1/50	2700	82	900	755	15000	5.16"
13 WATT	G24q-1	109035	PL13D/E/30/ECO	Soft White EOL	1/50	3000	82	900	755	15000	5.16"
13 WATT	G24q-1	109038	PL13D/E/35/ECO	White EOL	1/50	3500	82	900	755	15000	5.16"
13 WATT	G24q-1	109039	PL13D/E/41/ECO	Cool White EOL	1/50	4100	82	900	755	15000	5.16"
13 WATT	G24q-1	109122	PL13D/E/50/ECO	Natural White EOL	1/50	5000	82	900	755	15000	5.16"
18 WATT	G24q-2	109010	PL18D/E/27/ECO	Warm White EOL	1/50	2700	82	1200	1010	15000	5.75"
18 WATT	G24q-2	109012	PL18D/E/35/ECO	White EOL	1/50	3500	82	1200	1010	15000	5.75"
18 WATT	G24q-2	109013	PL18D/E/41/ECO	Cool White EOL	1/50	4100	82	1200	1010	15000	5.75"
18 WATT	G24q-2	109074	PL18D/E/50/ECO	Natural White EOL	1/50	5000	82	1200	1010	15000	5.75"
26 WATT	G24q-3	109090	PL26D/E/27/ECO	Warm White EOL	1/50	2700	82	1800	1515	15000	6.48"
26 WATT	G24q-3	109092	PL26D/E/35/ECO	White EOL	1/50	3500	82	1800	1515	15000	6.48"
26 WATT	G24q-3	109094	PL26D/E/41/ECO	Cool White EOL	1/50	4100	82	1800	1515	15000	6.48"
26 WATT	G24q-3	109096	PL26D/E/50/ECO	Natural White EOL	1/50	5000	82	1800	1515	15000	6.48"

Ordering Information

COMPACTS

Watt	Base	Product #	Product Code	Description	Pkg. Qty.	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg Rated Life	MOL (inc)
Triple Tube 4-Pin Electronic T4											
18 WATT	GX24q-2	44800	PL18T/E/27/ECO	Warm White EOL	1/50	2700	82	1200	1010	15000	4.57"
18 WATT	GX24q-2	44801	PL18T/E/35/ECO	White EOL	1/50	3500	82	1200	1010	15000	4.57"
18 WATT	GX24q-2	44803	PL18T/E/41/ECO	Cool White EOL	1/50	4100	82	1200	1010	15000	4.57"
18 WATT	GX24q-2	44804	PL18T/E/50/ECO	Natural White EOL	1/50	5000	82	1200	1010	15000	4.57"
26 WATT	GX24q-3	109020	PL26T/E/27/ECO	Warm White EOL	1/50	2700	82	1800	1515	15000	5.20"
26 WATT	GX24q-3	109022	PL26T/E/35/ECO	White EOL	1/50	3500	82	1800	1515	15000	5.20"
26 WATT	GX24q-3	109024	PL26T/E/41/ECO	Cool White EOL	1/50	4100	82	1800	1515	15000	5.20"
26 WATT	GX24q-3	109076	PL26T/E/50/ECO	Natural White EOL	1/50	5000	82	1800	1515	15000	5.20"
32 WATT	GX24q-3	109026	PL32T/E/27/ECO	Warm White EOL	1/50	2700	82	2400	2015	15000	5.79"
32 WATT	GX24q-3	109028	PL32T/E/35/ECO	White EOL	1/50	3500	82	2400	2015	15000	5.79"
32 WATT	GX24q-3	109030	PL32T/E/41/ECO	Cool White EOL	1/50	4100	82	2400	2015	15000	5.79"
32 WATT	GX24q-3	109070	PL32T/E/50/ECO	Natural White EOL	1/50	5000	82	2400	2015	15000	5.79"
42 WATT	GX24q-4	109032	PL42T/E/27/ECO	Warm White EOL	1/50	2700	82	3200	2690	15000	6.61"
42 WATT	GX24q-4	109034	PL42T/E/35/ECO	White EOL	1/50	3500	82	3200	2690	15000	6.61"
42 WATT	GX24q-4	109036	PL42T/E/41/ECO	Cool White EOL	1/50	4100	82	3200	2690	15000	6.61"
42 WATT	GX24q-4	109072	PL42T/E/50/ECO	Natural White EOL	1/50	5000	82	3200	2690	15000	6.61"
57 WATT	GX24q-5	44806	PL57T/E/27/ECO	Warm White EOL	1/50	2700	82	4200	3530	12000	7.80"
57 WATT	GX24q-5	44807	PL57T/E/41/ECO	Cool White EOL	1/50	4100	82	4200	3530	12000	7.80"
57 WATT	GX24q-5	44808	PL57T/E/50/ECO	Natural White EOL	1/50	5000	82	4200	3530	12000	7.80"
Spiral 4-Pin T3											
13 WATT	GX24q-1	109692	PL13SP/E/27	Warm White	1/50	2700	82	900	755	10000	3.50"
T3											
26 WATT	G24q-3	109696	PL26SP/E/27	Warm White	10/50	2700	82	1600	1345	10000	4.10"
26 WATT	G24q-3	109698	PL26SP/E/41	Cool White	10/50	4100	82	1600	1345	10000	4.10"
High Lumen Long 4-Pin T5											
18 WATT	2G11	109700	PLL18/835/ECO	White	10/40	3500	82	1250	1125	12000	8.94"
18 WATT	2G11	109702	PLL18/841/ECO	Cool White	10/40	4100	82	1250	1125	12000	8.94"
24 WATT	2G11	109704	PLL24/835/ECO	White	10/40	3500	82	1800	1620	12000	12.70"
24 WATT	2G11	109706	PLL24/841/ECO	Cool White	10/40	4100	82	1800	1620	12000	12.70"
36 WATT	2G11	109708	PLL36/835/ECO	White	10/40	3500	82	2800	2520	12000	16.45"
36 WATT	2G11	109710	PLL36/841/ECO	Cool White	10/40	4100	82	2800	2520	12000	16.45"
40 WATT	2G11	109712	PLL40/830/RS/ECO	Soft White	10/40	3000	82	3150	2835	20000	22.50"
40 WATT	2G11	109714	PLL40/835/RS/ECO	White	10/40	3500	82	3150	2835	20000	22.50"
40 WATT	2G11	109716	PLL40/841/RS/ECO	Cool White	10/40	4100	82	3150	2835	20000	22.50"
40 WATT	2G11	44900	PLL40/850/RS/ECO	Natural White	10/40	5000	82	3150	2835	20000	22.50"
55 WATT	2G11	109718	PLL55/835/ECO	White	10/40	3500	82	4700	4230	12000	21.20"
55 WATT	2G11	109720	PLL55/841/ECO	Cool White	10/40	4100	82	4700	4230	12000	21.20"
Flat Quad 4-Pin T5											
27 WATT	GX10q-4	109238	FML27/NDL	Natural White	1/50	5000	82	1700	1430	10000	5.90"

Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.