LED-8026 High Bay /Low Bay / Site

Stock No. LED-8026-NW LED-8026-DL **Product Description**

PT-120/277-100-300-NW (3000K) PT-120/277-100-300-DL (5700K) 100w = 250W

Description:

100W LED retrofit design replaces MH and HPS lamps up to 250w. Design features both down and side mounted LEDs delivering a wide, uniform light distribution. Suitable for fully enclosed high bay, low bay, canopy and other area fixtures.



- · Replaces up to a 250W HID
- 360° Illumination
- 120-277VAC, Non-Dimmable
- Available in 3000K or 5700K CCT
- >80 CRI
- 50,000 hr. rated L70 LED life
- Operating temp: -40°F 122°F
- UL Listed Damp (US & CA)
- 5 Year warranty

Applications:

LED High Bay / Low Bay / Canopy LED for HID retrofit lamps lower energy costs, bulb and ballast replacement costs and also can greatly reduce costly equipment rental when re-lamping HID lamps on and off cycle. LED for HID retrofits will also eliminate lamp disposal issues due to the mercury content of many HID lamps.

- High Bay
- Low Bay
- Gas / Bank Canopy fixtures
- Area / Site

Packaging: 4/Master CartonUnit: 10.25" x 10.25" x 10.24"
Master: 21.26" x 11.0 x 11.0"

Note: When retrofitting LED to HID fixture, ballast must be by-passed when present. Eliminating the ballast saves additional costs related to maintenance, energy consumption and performance. Additionally, by-passing ballast will insure no RFI interference.


Warranty

Warranty


Note: All specification is change without notice.

NOTE: Light Efficient Designated in the pending. Any use of these











c UL US

Technical Specifications				
Bulb Type	HID Retrofit	Mounting	E39	
Bulb Material	Aluminum/ Polycarbonate	LEDs:	300 Samsung #5630 SMD LED's	
Power Consumption	100 watts	Beam Angle	360°	
Lumens	3000K: 78000 Lm 5700K: 8000 Lm	Dimmable	No	
Efficacy	75 / 80 Lumens per watt	Replaces	Up to 250W HID	
Rated LED Life	Up to 50,000 Hrs.	сст	3000К 5700К	
Power Factor:	>99	CRI:	> 80	
IR / UV	None	Mercury/ Lead Content	None	
Warranty	5 year Limited	Dimensions	8.175" X 7.875"	

Note: All specification information falls within a \pm 2% range and is subject to change without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.

106 S. Wynstone Park Drive ● N. Barrington, IL 60010 (847) 380-3540 ● FAX: (847) 380-3542

www.led-llc.com