

PAR30S

LED

10.5 Watt PAR30S Specifications



The ETi 10.5 watt 525 lumen PAR30S LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. Integrated optical reflectors provides high quality point source beam versus pixelated designs. They are UL listed for use in dry locations and are RoHS compliant with no lead or mercury. Warranty is 3 years or 36 months.


KEY FEATURES & BENEFITS

- 10.5 Watt Low Power and High Performance
- 525 Lumens
- Dimmable
- 80 CRI
- 3000K
- Replaces most applications using 50w incandescent lamps
- Rated Lifetime: 40,000 hours



This light source meets restrictions on hazardous substances.

LAMP DIMENSIONS



SKU# 520266

Dimension A = 3.74"

Dimension B = 3.50"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us

APPLICATION INFORMATION

Indoor recessed can, high hat, ceiling mounted strip lighting and outdoor flood lighting applications in residential, office, retail, restaurant, school, hospital and hotel/motel locations.



10.5 Watt PAR30S

LED

SPECIFICATION DATA

Project _____

Item Number _____


Prepared by _____ Date _____

ORDERING INFORMATION

| Item Number | Description | Wattage | Base Type | Input Voltage (VAC) | Average Rated Life ¹ | Typical Lumens ² | CCT ³ | CBCP | Beam | R9 | Duv | CRI ⁴ | Power Factor | Operating Frequency |
|--|----------------------------------|---------|-----------|---------------------|---------------------------------|-----------------------------|------------------|------|------|----|---------|------------------|--------------|---------------------|
| 520266 | PAR30S 10.5 E26 DIM E83025 | 10.5 | E26 | 120 | 40,000 | 525 | 3000K | 2519 | 25° | 14 | -0.0027 | 80 | >0.85 | 60Hz |
| ¹ Hours lifetime with 70% lumen maintenance | | | | | | | | | | | | | | |
| ² Thermally stable typical lumens (±10%) | | | | | | | | | | | | | | |
| ³ Thermally stable CCT (±10%) | | | | | | | | | | | | | | |
| ⁴ Color rendering index/Ra | | | | | | | | | | | | | | |

SHIPPING INFORMATION

| Item Number | Item UPC | Item Dimensions (H x L x W) | Item Weight (lbs) | Inner Pack Qty | Inner Carton Bar Code | Inner Carton Dimensions (H x L x W) | Inner Pack Weight (lbs) | Master Pack Qty | Master Carton Bar Code | Master Dimensions (H x L x W) | Master Pack Weight (lbs) |
|-------------|------------------|-----------------------------|-------------------|----------------|-----------------------|-------------------------------------|-------------------------|-----------------|------------------------|-------------------------------|--------------------------|
| 520266 | 8366070 07209 | 4.3" x 4.0" x 4.0" | .6 | N/A | N/A | N/A | N/A | 12 | 50836607 007204 | 9.7" x 12.8" x 8.7" | 7.5 |



The Americas Headquarters
26650 Renaissance Parkway, STE 6
Cleveland, OH 44128

855-384-7754 www.etiled.us