CA10

LED

2.5 Watt CA10 Specifications



The ETi 2.5 watt 120 lumen CA10 LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. This CA10 Lamp has E12 base and comes with medium adapter (E26). They are UL listed for use in damp and dry locations and are RoHS compliant with no lead or mercury. Warranty period is 3 years or 36 months.

KEY FEATURES & BENEFITS

- 2.5 Watt Low Power and High Performance
- 120 Lumen
- 82 CRI
- 3000K
- UL Damp and Dry Locations
- Replaces most applications using 15w energy saving incandescent lamps
- Rated Lifetime: 25,000 hours










LAMP DIMENSIONS



SKU# 52301121

Dimension A = 1.99" Dimension B = 3.34"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us

APPLICATION INFORMATION

Chandeliers, bathroom vanity, accent lighting and general decorative indoor lighting in residential, office, retail, restaurant, school, hospital and hotel/motel locations.

855-384-7754 www.etiled.us

2.5 Watt CA10

LED

SPECIFICATION DATA

| Project | |
|-------------|------|
| Item Number | |
| Prepared by | Date |

ORDERING INFORMATION

| Model Number | Description | Wattage | Base Type | Input Voltage (VAC) | Average Rated Life ¹ | Typical Lumens ² | CCT ³ | R9 | DUV | СВСР | Beam | CRI ^{2.5} | Power Factor | Operating Frequency |
|-----------------|-------------------------|---------|--------------|---------------------------|---------------------------------------|--------------------------------|------------------|----|--------|------|------|--------------------|-----------------|------------------------|
| 52301121 | CA10 2.5 E12 E830FNA | 2.5 | E12 | 120 | 25,000 | 120 | 3000K | 19 | 0.0005 | 8.14 | 244° | 82 | >0.5 | 60Hz |

¹ Hours lifetime with 70% lumen maintenance

SHIPPING INFORMATION

| | | | | | | | Inner | | | | |
|----------|--------|-------------------------|--------|-------|----------|--------------|--------|--------|----------|----------------|--------------|
| | Item | | Item | Inner | Inner | Inner Carton | Pack | Master | Master | Master Dimen- | Master |
| Model | UPC | Item Dimensions | Weight | Pack | Carton | Dimensions | Weight | Pack | Carton | sions | Pack |
| Number | | $(H \times L \times W)$ | (lbs) | Qty | Bar Code | (H x L x W) | (lbs) | Qty | Bar Code | (H x L x W) | Weight (lbs) |
| | | | | | | | | | | | |
| | 836607 | | | | 30836607 | 4.4" x 14" x | | | 50836607 | 9.0" x 14.7" x | |
| 52301121 | 006509 | 4" x 2.2" x 2.2" | 0.16 | 12 | 006500 | 5.6" | 2.2 | 48 | 006504 | 11.7" | 10 |



The Americas Headquarters 26650 Renaissance Parkway, STE 6 Cleveland, OH 44128

855-384-7754

www.etiled.us

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra