

Project:	Toshiba Lamp:
Type:	Notes:

Ordering Information

Ordering Code	Input Voltage (VAC)	Lamp Shape	Base Type	CCT ¹	Initial Lumens (lm) ²	Wattage (W)	Lamp Efficacy (lm/W)	Rated Life (hrs) ³	CRI	Power Factor	Equivalency ⁴	Lamp Weight lb (g)	Dimmable	ENERGY STAR
11BR30/27J-T	120	BR30	E26	2700K	820	11.0	74.5	40,000	82	0.96	65W Halogen	0.72 (327)	Yes	Testing
11BR30/40K-T	120	BR30	E26	4000K	920	11.0	83.6	40,000	81	0.96	65W Halogen	0.72 (327)	Yes	Testing


- CCT Range complies to ANSI C78.377-2008.
- Thermally stable typical lumens ($\pm 10\%$)
- Rated life is based on 70% lumen maintenance and engineering testing and probability analysis; life hours per ENERGY STAR[®] may vary.
- Equivalency based on the ENERGY STAR[®] Integral LED Lamp V1.0 Draft 4 Specification (4/19/2013)

Note: All information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility. All lamps meet ENERGY STAR Integral LED Lamp requirements and will be submitted for testing. Five-year warranty based on 12 hr/day usage. Toshiba LED Lighting Systems Division reserves the right to make changes and/or improvements in designs and/or dimensions without notice or obligation.



Dimensions

Model BR30
MOL (A) 5.29" (134.4 mm)
Diameter (B) 3.74" (95.0 mm)



Note: Lamp shape conforms to ANSI C78.21-2003. Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Ordering Code	50W Halogen	65W Halogen
11BR30/27J-T	\$171.60	\$237.60
11BR30/40K-T	\$171.60	\$237.70

Note: Energy savings based on using one bulb for 40,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.