TOSHIBA Leading Innovation >>>

Project:	Toshiba Lamp:				
Туре:	Notes:				



	Ordering Code	Input Voltage (VAC)	Lamp Shape	Base Type	CCT ¹	Initial Lumens (Im)²	Wattage (W)	Lamp Efficacy (Im/W)	Rated Life (hrs) ³	CRI	Power Factor	Equivalency⁴	Lamp Weight Ib(g)	Dimmable	Energy ENERGY STAR
	8G25/27F-UP	120	G25	E26	2700K	420	8.3	50.6	40,000	85	0.77	40W Incandescent	0.31 (141)	Yes	•
מ	8G25/40F-UP	120	G25	E26	4000K	450	8.3	54.2	40,000	85	0.77	40W Incandescent	0.31 (141)	Yes	•

1. CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens (± 10%)

 Rated life is based on 70% lumen maintenance and engineering testing and probability analysis; life hours per ENERGY STAR[®] may vary.


4. Equivalency based on the ENERGY STAR® Integral LED Lamp criteria for decorative lamps.



Note: All information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility. All lamps meet ENERGY STAR Integral LED Lamp requirements and will be submitted for testing. Five-year warranty based on 12 hr/day usage. Toshiba LED Lighting Systems Division reserves the right to make changes and/or improvements in designs and/or dimensions without notice or obligation.







5

Note: Lamp shape conforms to ANSI C78.21-2003. Designed to comply with RoHS Directive 2002/95/EC.

S
G
2
>
Ø
S
σ
5
e
2
ш

Dimensions

 Ordering Code
 40W Incandescent

 8G25/27F-UP
 \$139.48

 8G25/40F-UP
 \$139.48

Note: Energy savings based on using one bulb for 40,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.