#### www.etiled.us

# **PAR38 40°**

# LED

### 16 Watt PAR38 Specifications




The ETi 16 watt PAR38 LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. Integrated optical reflectors provides high quality point source beam versus pixilated designs. They are UL listed for use in dry locations and are RoHS compliant with no lead or mercury. Warranty is 3 years or 36 months.

#### **KEY FEATURES & BENEFITS**

- 16 Watt Low Power and High Performance
- 960 Lumen
- Dimmable
- 83 CRI
- 3000K
- Replaces most applications using 70w incandescent lamps
- Rated Lifetime: 40,000 hours



#### LAMP DIMENSIONS



SKU# 520245

Dimension A = 4.62" Dimension B = 5.50"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us

#### **APPLICATION INFORMATION**

Indoor recessed can, high hat, ceiling mounted strip lighting and outdoor flood lighting applications in residential, office, retail, restaurant, school, hospital and hotel/motel locations.



855-384-7754 www.etiled.us

520245 Updated 1/14/2013

## 16 Watt PAR38

#### SPECIFICATION DATA

Project \_\_\_\_\_

Item Number\_\_\_\_\_

Prepared by\_\_\_\_\_

\_Date\_\_\_\_\_

LED

#### ORDERING INFORMATION

ltem Number	Description	Wattage	Base	Input Voltage (VAC)	4	Typical Lumens <sup>2</sup>	CCT <sup>3</sup>	CBCP	Beam	R9	Duv			Operating Frequency
520245	PAR38 16 E26 DIM E830S40 Silver body	16	E26	120	40,000	960	3000K	1453	40°	26	0.0032	83	>0.85	60Hz
<sup>1</sup> Hours lifetime with 70% lumen maintenance														
<sup>2</sup> Thermally stable typical lumens (±10%)														
<sup>3</sup> Thermally stable CCT (±10%)														
<sup>4</sup> Color rendering index/Ra														

#### SHIPPING INFORMATION

								Inner				
		Item			Inner	-	Inner Carton	Pack	Master		Master Dimen-	
	Item			Weight	Pack		Dimensions				sions	Pack
	Number		(HxLxW)	(lbs)	Qty	Bar Code	(H x L X W)	(lbs)	Qty		· /	Weight (Ibs)
		8366070								50836607	12.5" x 14.9" x	
	520245	07056	5.7" x 4.7" x 4.7"	.74	N/A	N/A	N/A	N/A	12	007051	10.3"	10.2
Light Output (Lumens) 960   Watts 960   Watts 16   Color Accuracy 83   Witts 3000 (Br/(plt White))   Visit State and and many 83   Witts 3000 (Br/(plt White))   Visit State and and many 600   Visit State and and many 600   Visit was applied backs for the Labor Arterscore Gaude. 266500 Renaissance Park   Calescore White Calescore Many (Britted State)   Watts Cales									nce Park			
					855	-384-7	754 w	ww.e	etilec	l.us		

520245 Updated 1/14/2013