

PROMOLUX

THE SCIENCE OF FOOD SAFE LIGHTING

PLATINUM T12 LAMPS SAFETY COATED



Lamp Type	Part Number	Lamp Watts	Nominal Length		Diameter		Contact Pins	Avg Life Hrs	Box Qty
			(mm)	(in)	(mm)	(in)			
F20 T12	C11020	20	600	24	38	1 1/2	MBP	10,000	12
F30 T12	C11030	30	900	36	38	1 1/2	MBP	20,000	12
F40 T12	C11040	40	1200	48	38	1 1/2	MBP	20,000	25
F48 T12 SL	C11048	40	1150	46	38	1 1/2	SP	10,000	12
F60 T12 SL	C11060*	50	1500	60	38	1 1/2	SP	12,000	12
F72 T12 SL	C11072-4	55	1800	72	38	1 1/2	SP	12,000	4
F96 T12 SL	C11096-4	75	2400	96	38	1 1/2	SP	18,000	4
F48 T12 HO	C11148*	60	1150	46	38	1 1/2	RDC	10,000	12
F60 T12 HO	C11160*	75	1500	60	38	1 1/2	RDC	12,000	12
F72 T12 HO	C11172-4	85	1800	72	38	1 1/2	RDC	12,000	4
F96 T12 HO	C11196-4	110	2400	96	38	1 1/2	RDC	12,000	4

PROMOLUX PLATINUM T12 Lamps are typically found in older cases especially in the 3ft and 4ft variety. They are also commonly used as overhead lighting in meat departments. The high output (HO) lamps are most often used in many older upright low temp (freezer) cases.

*While quantities last; box sizes may vary.