LED Series

Large LED Box Mount Vaporproof



VB43

Housing:

Heavy Duty Die Cast Aluminum Housing & Screw On Guard, Chromate Conversion Coating, Repaintable Textured Gray Powdercoat Finish, ¾" NPS Threaded Mounts. Includes Weatherproof Box with Coin Plugs

Lens:

Clear Glass Globe

Mounting:

Mounts on Electrical Box or Pendant Mount

LG LED Module:

Luminous Flux: See Chart

CRI: 70+, CCT: 4000K, 5700K or 6500K Operating Temperature: -40 ≈ 50°C

50,000 Hours

Module has IP67 Rating

RoHS Compliant

Wattage:

LED: 1 x 9 or 12w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings:

CSA: Listed for Wet Locations

Options:

Dimmable Driver

Custom Colors Available Upon Request.

Large LED Box Mount Vaporproof

Catalog #

Description

Complete Units

Ordering Information


Example: VB43LF1X12U4KGSF

| andmpro: TE | Example: 12 loci 1/120 incol | | | | |
|-------------|------------------------------|--------------------------------|--|--|--|
| VB43 | Model: | VB43 | | | |
| L | LED Mfr: | L=LG Innotek | | | |
| F | Optics: | F=Medium Beam Spread | | | |
| 1X | Number of Modules: | 1X=One | | | |
| 12 | Wattage: | 9=9w, 12=12w | | | |
| U | Ballast: | U=120-277V | | | |
| 4K | Color Temp: | 4K=4000K, 57K=5700K, 65K=6500K | | | |
| G | Color: | G=Gray | | | |
| | Mounting: | N/A | | | |
| SF | Options: | SF=Single Fuse, DF=Double Fuse | | | |
| | | | | | |

Total Luminous Flux per Module

| | | Optic Type | | | | | | |
|-----|-------|------------|-----|------|-----|------|-----|--|
| | | С | | F | | 1 | | |
| | | 12w | 9w | 12w | 9w | 12w | 9w | |
| сст | 6500K | 1288 | 850 | 1345 | 888 | 1296 | 856 | |
| | 5700K | 1288 | 850 | 1345 | 888 | 1296 | 856 | |
| | 4000K | 1076 | 710 | 1100 | 726 | 1088 | 718 | |

DIMENSIONS



| Catalog # | Description |
|-----------|---|
| VS30S | Straight Stamped Aluminum Shade for VP/VB30 Series, Repaintable Textured Gray Finish |
| VS30A | Angled Stamped Aluminum Shade for VP/VB30 Series, Repaintable Textured Gray Finish |
| VWGS | Wire Guard for Straight Shade, Stainless Steel |
| VWGA | Wire Guard for Angled Shade, Stainless Steel |
| VG30 | Heat-Treated Clear Glass Globe |
| VG30F | Frosted Glass Globe |
| VP3G | Cast Guard |
| CPSPR | Swivel Pendant Mount - Round, for Angled or Straight Ceilings, Fits ¾" Conduit, Includes Reducer Bushing (to ½") & Set Screw |
| CPSPS | Swivel Pendant Mount - Square, for Angled or Straight Ceilings, Fits ¾" Conduit; Includes Reducer Bushing (to ½") & Set Screw |
| CPRB | Reducer Bushing, ¾" to ½", Use with Swivel Mount |
| CPRB1 | Die Cast Round Electrical Box with Five (5) 1/2" Coin Plugs |
| CPRC1 | Backplate, ½" Coin Plugs |
| CPRB3 | Die Cast Round Electrical Box with Five (5) 3/4" Coin Plugs |

LED Series

Large LED Box Mount Vaporproof





VS30S

VS30A





VWGS (Shown Mounted)

VWGA (Shown Mounted)





VG30, VG30F

VP3G





CPSPR

CPSPS





CPRB

CPRB1





CPRC1

CPRB3