LED Series

LED Crescent Wall Sconce Down Light



WP35

Housing:

Die Cast Housing, Textured Bronze Powdercoat Finish Over a Chromate Conversion Coating Mounting:

Mount Over a 4" Recessed Outlet Box Includes Easy-Hang "Two Hands Free" Wall Mounting Bracket

LG LED Module:

Luminous Flux: See Chart

CRI: 70+, CCT: 4000K, 5700K or 6500K Operating Temperature: -40 ≈ 50°C

50,000 Hours

Module has IP67 Rating

RoHS Compliant

Wattage:

LED: 3 x 9 or 12w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings: CSA: Listed for Wet Locations

LM-79 Report Available on Select Models.

Options:

Dimmable Driver 2.5KV Surge Protection

Custom Colors Available Upon Request.


LED Crescent Wall Sconce Down Light Catalog # Example: WP35LF3X12U4KZSP **WP35** Model: LED Mfr: L=LG Innotek F Optics: F=Medium Beam Spread Number of 3X 3X=Three Modules: 12 Wattage: 9=9w, 12=12w U=120-277V U Ballast: 4K CCT: 4K=4000K, 57K=5700K, 65K=6500K z Color: Z=Bronze Mounting: N/A SF=Single Fuse, DF=Double Fuse, SP Options: SP=Surge Protection



Total Luminous Flux per Module		Optic Type					
		С		F		1	
		12w	9w	12w	9w	12w	9w
сст	6500K	1288	850	1345	888	1296	856
	5700K	1288	850	1345	888	1296	856
	4000K	1076	710	1100	726	1088	718



LD



WP35LF3X12

LED Series LED Crescent Wall Sconce **Down Light** REV. 08-07-12



LM-79 Report Available.