



# MasterColor CDM ED17 Protected Elite 4200K

MasterColor CDM 70W ED17P CL U ELITE/4K

MasterColor Elite Protected Ceramic Metal Halide ED-17 4200K  
Lamps provide excellent lumen maintenance and outstanding performance over time in a protected lamp.

## Product data

### • General Characteristics

|                                |                                      |
|--------------------------------|--------------------------------------|
| Base                           | Medium [Single Contact Medium Screw] |
| Base Information               | Brass [Brass Base]                   |
| Bulb                           | ED17P [Protected]                    |
| Bulb Material                  | Hard Glass                           |
| Bulb Finish                    | Clear                                |
| Operating Position             | Universal [Any or Universal (U)]     |
| Main Application               | General Lighting                     |
| RatedAvgLife(See Family Notes) | 20000 hr                             |

|                        |             |
|------------------------|-------------|
| Lamp Voltage           | 100 V       |
| Lamp Current           | 0.9 A       |
| Ignition Time          | 10 (max) s  |
| Re-ignition Time [min] | 8 (max) min |

### • Environmental Characteristics

|                         |              |
|-------------------------|--------------|
| Mercury (Hg) Content    | 7.1 (max) mg |
| Picogram per Lumen Hour | 76 p/LuHr    |

### • Light Technical Characteristics

|                              |                                       |
|------------------------------|---------------------------------------|
| Color Code                   | 940 [CCT of 4000K]                    |
| Color Rendering Index        | 89 (min), 92 (nom) Ra8                |
| Color Designation            | Cool White                            |
| Color Temperature            | 4000 K                                |
| Color Temperature technical  | 4000 K                                |
| Initial Lumens               | 6200 Lm                               |
| Luminous Efficacy Lamp       | 88 Lm/W                               |
| Lumen Maintenance - 10% life | 90 %                                  |
| Lumen Maintenance - 40% life | 80 %                                  |
| Design Mean Lumens           | 4960 Lm                               |
| Chromaticity Coordinate X    | 0.368 (min), 0.377 (nom), 0.386 (max) |
| Chromaticity Coordinate Y    | 0.354 (min), 0.360 (nom), 0.366 (max) |

### • UV-related Characteristics

|                    |                        |
|--------------------|------------------------|
| Damage Factor D/fc | 0.28 -                 |
| PET (NIOSH)        | 347 h500lx             |
| UV A               | 9.2 mW/cm <sup>2</sup> |
| UV B               | 0 mW/cm <sup>2</sup>   |
| UV C               | 0 mW/cm <sup>2</sup>   |

### • Luminaire Design Requirements

|                      |             |
|----------------------|-------------|
| Cap-Base Temperature | 190 (max) C |
| Bulb Temperature     | 400 (max) C |

### • Product Dimensions

|                              |                |
|------------------------------|----------------|
| Light Center Length L        | 3.438 in       |
| Max Overall Length (MOL) - C | 5.438 (max) in |
| Diameter D                   | 2.125 in       |

### • Electrical Characteristics

|       |      |
|-------|------|
| Watts | 70 W |
|-------|------|

**PHILIPS**

# MasterColor CDM ED17 Protected Elite 4200K

## • Product Data


Product number 429950  
Full product name MasterColor CDM 70W ED17P CL U ELITE/4K  
Short product name MHC70/U/MP/4K ELITE  
Pieces per Sku 1

Skus/Case 12  
Bar code on pack 46677429959  
Bar code on case 50046677429954  
Logistics code(s) 928601177901  
eop\_net\_weight\_pp 0.001 kg

## Dimensional drawing

### MasterColor CDM 70W ED17P CL U ELITE/4K

| Product                            | C (Max) | D (Norm) |
|------------------------------------|---------|----------|
| MHC P 70W/940 E26 ED17P CL U ELITE | 5.438   | 2.125    |



E26



© 2013 Koninklijke Philips N.V. (Royal Philips)  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2013, October 4  
data subject to change