

# NS-18

## 4" Adjustable Eyeball

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Metal trim with adjustable eyeball can be rotated 358° horizontally and 15° vertically. Eyeball allows lamp to be mounted inside and adjust with trim.

**Mounting:** Trim includes three trim clips that securely mount trim in housing. Remove socket from plate and mount directly onto eyeball.

### COMPATIBLE LAMP / HOUSINGS

#### Line Voltage:

15W R20/PAR20 max. (NS-401AT/IC)

35W R20/PAR20 max. (NFBIC-4INCATA)

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)

See individual housing specification sheets for more information.

### LABELS AND LISTINGS

\* cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES & DIMENSIONS




NS-18



NS-18B



NS-18BZ



### 4" Surface Gimbal Ring

Catalog No.

**NS-18** = 4" White Adjustable Eyeball

**NS-18B** = 4" Black Adjustable Eyeball

**NS-18BZ** = 4" Bronze Adjustable Eyeball

### Compatible Housings

Catalog No.

**NFBIC-4INCATA** = 2-Hour Fire Rated New Construction / 35W max.

**NS-401QAT** = Non-IC Air-Tight New Construction / 50W max

**NS-401QAT/IC** = IC Air-Tight New Construction / 15W max

**NSIC-401QAT** = IC Air-Tight New Construction / 50W max

**NSR-404QAT** = Non-IC Air-Tight Remodel / 50W max

**NSRIC-404QAT** = IC Air-Tight Remodel / 50W max

Example: **NS-18** = 4" White Adjustable Eyeball