


**NS-42 / NS-43 / NS-44  
NS-46 / NS-52 / NS-53  
Reflector with Ring**

Type
Project
Catalog No.
Lamp/Wattage

**TRIM DIMENSIONS**



Trim OD: 5"  
Aperture: 3-1/2"  
Height: 2"

**FEATURES**

**Trim**  
Precision spun 0.050 aluminum high grade reflector. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

**Mounting**  
Trim includes three trim clips that securely mount trim in housing.

**Compatible Housings**  
Compatible with Line Voltage, Compact Fluorescent, and GU24 Compact Fluorescent housings. See individual specification sheets for more information.

**Lamp**  
**Line Voltage**  
50W R20/PAR20 Max. (NS-401QAT; NSIC-401QAT; NSR-404QAT)  
**Compact Fluorescent**  
13W Quad/Triple (NS-406Q; NS-406EL; NSR-408Q; NSR-408EL)  
**GU24 Compact Fluorescent**  
13W-26W GU24 (NHRIC-4G24AT, NHRIC-4G24AT)

**Labels and Listings**  
cULus Listed for Damp Location when used with compatible housing.

**Reflector with Ring**

- NS-42:** Specular Gold Reflector with White Metal Ring
- NS-42G:** Specular Gold Reflector with Gold Metal Ring
- NS-43:** Specular Black Reflector with White Metal Ring
- NS-43B:** Specular Black Reflector with Black Metal Ring
- NS-44:** Specular Clear Reflector with White Metal Ring
- NS-44C:** Specular Clear Reflector with Chrome Metal Ring
- NS-44HZ:** Haze Reflector with White Metal Ring
- NS-44N:** Specular Clear Reflector with Natural Metal Ring
- NS-46:** Specular White Reflector with White Metal Ring
- NS-52:** Natural Metal Reflector with Natural Metal Ring
- NS-53:** Copper Reflector with Copper Metal Ring
- NS-53BZ:** Bronze Reflector with Bronze Metal Ring

**Compatible Housings**

LINE VOLTAGE			
Item Number	Installation Type	Lamp	Dimensions
<input type="checkbox"/> <b>NS-401QAT</b>	Non-IC Air-Tight New Const.	50W R/PAR20	W: 5-5/8" L: 8-1/2" H: 5-5/8"
<input type="checkbox"/> <b>NSIC-401QAT</b>	IC Air-Tight New Construction	50W R/PAR20	W: 5-1/4" L: 8-1/2" H: 6-3/8"
<input type="checkbox"/> <b>NSR-404QAT</b>	Non-IC Air-Tight Remodel	50W R/PAR20	W: 4-1/4" L: 11-1/4" H: 5-5/8"
COMPACT FLUORESCENT			
<input type="checkbox"/> <b>NS-406Q</b>	Non-IC New Constr., Magnetic	13W Quad	W: 6-1/4" L: 10" H: 5-1/2"
<input type="checkbox"/> <b>NS-406EL</b>	Non-IC New Constr., Electronic	13W Quad/Triple	W: 6-1/4" L: 9" H: 5-1/2"
<input type="checkbox"/> <b>NSR-408Q</b>	Non-IC Remodel, Magnetic	13W Quad	W: 4-3/4" L: 11-7/8" H: 5-1/2"
<input type="checkbox"/> <b>NSR-408EL</b>	Non-IC Remodel, Electronic	13W Quad/Triple	W: 4-3/4" L: 11-7/8" H: 5-1/2"
GU24 COMPACT FLUORESCENT			
<input type="checkbox"/> <b>NHRIC-4G24AT</b>	IC Air-Tight New Construction	13W-26W GU24	W: 6-1/4" L: 13-1/4" H: 6-3/8"
<input type="checkbox"/> <b>NHRIC-4G24AT</b>	IC Air-Tight Remodel Housing	13W-26W GU24	W: 4-1/4" L: 13" H: 6-3/8"