

NT-23 / NP-23

6" Fresnel Lens with Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: High grade fresnel lens attached to trim. Lens can be easily removed by hand without tools from below the ceiling for relamping.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86)..

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

25W A19 Maximum (NHIC-27QAT; NHRIC-27QAT)

40W A19 Maximum (NHIC-17QAT; NHIC-926QAT; NHRIC-17QAT; NHRIC-926QAT)

60W A19 Max. (NH-26Q; NH-27Q; NHIC-17/100DWQA; NHR-26Q; NHR-27Q)

See individual housing specification sheets for more information.

LABELS AND LISTINGS

* cULus Listed for Wet Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



NT-23



NT-23B




NT-23BZ



NT-23N



NP-23



6" Fresnel Lens with Trim

Catalog No.

NT-23 = 6" Fresnel Lens with White Metal Trim

NT-23B = 6" Fresnel Lens with Black Metal Trim

NT-23BZ = 6" Fresnel Lens with Bronze Metal Trim

NT-23N = 6" Fresnel Lens with Natural Metal Trim

NP-23 = 6" Fresnel Lens with White Plastic Trim

Compatible Housings

Catalog No.

NH-26Q = Non-IC New Construction / 60W max

NHR-26Q = Non-IC Remodel / 60W max

NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 60W max

NHIC-17QAT = IC Air-Tight New Construction / 40W max

NHRIC-17QAT = IC Air-Tight Remodel / 40W max

NH-27Q = Shallow Non-IC New Construction / 60W max

NHR-27Q = Shallow Non-IC Remodel / 60W max

NHIC-27QAT = Shallow IC Air-Tight New Construction / 25W max

NHRIC-27QAT = Shallow IC Air-Tight Remodel / 25W max

NHIC-926QAT = Sloped IC Air-Tight New Construction / 40W max

NHRIC-926QAT = Sloped IC Air-Tight Remodel / 40W max

Example: **NT-23** = 6" Fresnel Lens with White Metal Trim