LED-8029E Post Top / Bollard / Wall Pack



<u>SKU (USA)</u> LED-8029E30 LED-8029E42 LED-8029E57
 SKU (Canada)
 Des

 LED-8029E30C
 24W

 LED-8029E42C
 24W

 LED-8029E57C
 24W

Description 24W 3000K 24W 4200K 24W 5700K

Technical Specifications			
Models US/CAN	LED-8029E30/ LED-8029E30C	LED-8029E42/ LED-8029E42C	LED-8029E57/ LED-8029E57C
ССТ	3000K	4200K	5700K
Power Consumption	24 watts		
Replaces	100w MH/HPS		
Mounting	E26		
Voltage	120-277VAC (USA) 120-347VAC (CANADA)		
LED Type	50 Samsung #5630 SMD		
Beam Angle	360		
Dimmable	No		
Operating Temp	-40°F - +122°F		
Rated R70 Life	Up to 50,000 Hrs.		
Warranty	5 Year Limited*		
LM79			
Specifications	Yes	Yes	Yes
Power (W)	24.1	23.2	25.1
ССТ	3287	4340	5704
Light Output	2320	2319	2366.4
Efficacy	96.3	99.99	94.28
THD @ 277V	17.94%	19.97%	15.46%
PF @ 277V	0.953	0.948	0.959
CRI:	84.5	0.844	85.6
R9	15	16	34
Duv	-0.0017	-0.007	0.0028
Packaging	9 / Master Carton		
Unit	4.7" x 4.7" x 8.86" 1.14 lbs.		
Master	14.8" x 14.8" x 9.5" 11.4 lbs.		
Note: All specification information falls within $a + 2\%$ range and is			

Note: All specification information falls within a \pm 2% range and is subject to change without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America,



CONTROL CONTRO

Description:

24W LED retrofit lamp to replace MH and HPS lamps up to 100w, E26 Medium base. Integrated insect/dust screen. UL damp rated approved for <u>fully enclosed</u> fixtures.

с.

Features:

- Replaces 100w HID Lamps
- 120-277V or 120-347V (Canada)
- UL approved for fully enclosed fixtures and damp environments (USA & Can)
- Active Cooling Fan >70,000 hr. rated life
- 50,000 rated life
- 5 year limited warranty (see website for details)

Applications:







Post Top

Wall Pack

Installation Notes:

- When installing LED-8000 series retrofit lamps within HID fixtures, **ballast must be bypassed** when present.
- 8000 series retrofits are UL damp rated, sealing the fixtures after installation will deliver best results.
- Installing surge/lightning protectors is highly recommended and helps to eliminate premature driver failure caused by surges and other power fluctuations.

188 S. Northwest Highway • Cary, IL 60013 (847) 380-3540 • FAX: (847) 380-3542 www.led-llc.com