

Project:	Toshiba Lamp:
Type:	Notes:

BR40

Ordering Information

Ordering Code	Input Voltage (VAC)	Lamp Shape	Base Type	CCT ¹	Initial Lumens (lm) ²	Wattage (W)	Lamp Efficacy (lm/W)	Rated Life (hrs) ³	CBCP (cd)	Power Factor	Equivalency ⁴	Lamp Weight lb (g)	Dimmable	ENERGY STAR
13BR40/27K-T	120	BR40	E26	2700K	950	13.0	73.1	40,000	82	0.98	65W Halogen	1.39 (630)	Yes	●
13BR40/40L-T	120	BR40	E26	4000K	1050	13.0	80.9	40,000	81	0.98	65W Halogen	1.39 (630)	Yes	●
20BR40/27M-T	120	BR40	E26	2700K	1330	20.0	66.5	40,000	80	0.90	90W Halogen	1.45 (658)	Yes	Testing
20BR40/40M-T	120	BR40	E26	4000K	1400	20.0	70.0	40,000	80	0.90	90W Halogen	1.45 (658)	Yes	Testing

- CCT Range complies to ANSI C78.377-2008.
- Thermally stable typical lumens (± 10%)
- Rated life is based on 70% lumen maintenance and engineering testing and probability analysis; life hours per ENERGY STAR® may vary.
- Equivalency based on the ENERGY STAR® Integral LED Lamp criteria for directional lamps.


Note: All information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility. All lamps meet ENERGY STAR Integral LED Lamp requirements and will be submitted for testing. Five-year warranty based on 12 hr/day usage. Toshiba LED Lighting Systems Division reserves the right to make changes and/or improvements in designs and/or dimensions without notice or obligation.



DAMP RATED 5 FIVE YEAR WARRANTY lighting facts UL US LISTED

Dimensions

Model BR40
MOL (A) 6.50" (165.1 mm)
Diameter (B) 4.88" (123.96 mm)



Note: Lamp shape conforms to ANSI C78.21-2003. Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Ordering Code	50W Incandescent	65W Incandescent	90W Incandescent
13BR40/27K-T	\$162.80	\$228.80	—
13BR40/40L-T	\$162.80	\$228.80	—
20BR40/27M-T	\$132.00	\$198.00	\$308.00
20BR40/40M-T	\$132.00	\$198.00	\$308.00

Note: Energy savings based on using one bulb for 40,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.