















# PHOTOLUMINESCENT EXIT SIGNS

FREELITE™ Photoluminescent Emergency Exit Signs require no electrical power for operation other than the normal ambient light in your building. FREELITE signs absorb light, then their self-illuminating materials shine bright when the lights go out. They eliminate costly testing & maintenance, install quickly and have no electrical circuits to fail in emergencies. They are also LEED points qualified and Tritium-free (non-radioactive).

- No additional electricity required (stores and re-emits ambient light; minimum 5 footcandles required)
- Extremely low maintenance (no batteries or lamps to fail, no periodic testing required)
- Easy, quick installation (uses standard mounting brackets)
- Non-radioactive (Tritium-free) / Fully recyclable and environmentally friendly
- Many styles, viewing distances, and colors
- Made in the U.S.A.





## **PHOTOLUMINESCENT**













#### **FEATURES**


- · LEED points qualified
- Manufactured in the United States
- Reduces emergency generator loads
- · Architectural and aesthetically pleasing designs
- Meets low location egress requirements
- · Flexibility of design

- No energy cost Uses no electricity (Requires 5fc ambient light)
- No maintenance cost
- No disposal cost
- · Reduces overhead costs
- Non-radioactive (Tritium free)
- Recyclable
- · Lower labor and material cost
- · No conduit or wire to run
- · No emergency circuit required
- · Standard bracket options for easy mounting



#### 50' Viewing Distance with PL Legend

| SERIES  | # of Faces | BACKGROUND COLOR      | FRAME COLOR            |
|---------|------------|-----------------------|------------------------|
| FLPL50* | S = SINGLE | G = GREEN             | BLANK = NO FRAME       |
| FLPLMB* | D = DUAL   | R = RED               | B = BLACK              |
|         |            | B = BLACK             | G = GREEN              |
|         |            | SR = BRUSHED ALUMINUM | R = RED                |
|         |            | W/ RED LETTER OUTLINE | S = SILVER POWDER COAT |
|         |            | SG = BRUSHED ALUMINUM | W – WHITE              |





### 50' Viewing Distance, Vandal Resistant with PL Legend

| SERIES  | # of Faces | BACKGROUND COLOR | FRAME COLOR            |
|---------|------------|------------------|------------------------|
| FLPL51* | S = SINGLE | G = GREEN        | B = BLACK              |
|         | D = DUAL   | R = RED          | G = GREEN              |
|         |            | B = BLACK        | R = RED                |
|         |            |                  | S = SILVER POWDER COAT |
|         |            |                  | W = WHITE              |



#### 75' Viewing Distance with PL Background

| SERIES  | # of Faces | LETTER COLOR | FRAME COLOR            |
|---------|------------|--------------|------------------------|
| FLPL75* | S = SINGLE | G = GREEN    | BLANK = NO FRAME       |
| FLPLMB* | D = DUAL   | R = RED      | B = BLACK              |
|         |            |              | G = GREEN              |
|         |            |              | R = RED                |
|         |            |              | S = SILVER POWDER COAT |
|         |            |              | W = WHITE              |



### 100' Viewing Distance with PL Legend

| SERIES  | # of Faces | BACKGROUND COLOR | FRAME COLOR            |
|---------|------------|------------------|------------------------|
| FLPL10* | S = SINGLE | G = GREEN        | BLANK = NO FRAME       |
| FLPLMB* | D = DUAL   | R = RED          | B = BLACK              |
|         |            | W = WHITE        | G = GREEN              |
|         |            | B = BLACK        | R = RED                |
|         |            |                  | C - CILVED DOWNED COAT |

MOUNTING BRACKETS For use with framed signs

**COLOR** MODEL

FLPLMB\* For FLPL50 and FLPL75 signs FLPLMB10\* For FLPL10 signs only

B - Black S - Silver

R - Red

W - White G - Green



 $\mathsf{W} = \mathsf{WHITE}$ 

\*Options available for quick ship are bolded.



