

Project	Type

## DESCRIPTION

Flat Panel (FLP) is an LED troffer luminaire designed for installation in 2-foot by 2-foot conventional suspended grid ceilings for new construction or retrofit projects. Featuring superior, evenly dispersed lighting that sets the standard in performance for solid state ceiling luminaires, FLP can also significantly reduce the number of fixtures needed to light a given area. Custom fixture and power supply kit design allows for quick and easy installation, reducing costly labor time. The superior thermal design will extend both the life of the fixture and power supply. And by still emitting 70% of the original light output after more than 239,000 hours\*\*, FLP will last many years without the need for costly replacement or maintenance.

## FEATURES

- Phenomenal light output using only 36 Watts or 45 Watts
- Sealed, type Non-IC fixture
- Class 2 compliant design (low voltage, limited power)
- L70 lifetime of more than 239,000 hours\*\* with 36 Watts; 173,000 hours\*\* with 45 Watts.
- Fixture dimmable via Mark 7 (0-10V) dimming interface
- 5-year warranty

## CERTIFICATION

- UL Listed (UL 1598, file #: E344008)
- DLC approved
- NSF approved
- CEC approved
- C-Tick certified
- LM-79 available



## FLAT PANEL FLP

2' x 2' Troffer, Flat Panel  
36 W / 3600 Lumens  
45 W / 4250 Lumens



ENERGY DATA	36 Watt	45 Watt
CCT (K)	4000	4000
Input Voltage (VAC)	120 - 277	120 - 277
System Level Power (W)*	36	45
Delivered Lumens (Lm)	3600	4250
System Efficacy (Lm/W)*	100	94
Color Rendering Index	80 min	80 min
L70 Calculated Life (Hrs)**	239,000	173,000
L85 Calculated Life (Hrs)**	110,000	79,000
Operating Temp (°C)	-30 to 50	-30 to 50

\* Measured at 277VAC

\*\* Projected LED lumen maintenance based on the IES TM-21 model. Calculation is based on 10,000 hours of LM-80 data. Fixture average ambient temperature is 25°C.

## FIXTURE ORDERING INFORMATION

Example: FLP-22L-36W3600L-40K-EM

FLP	22L		40K	
Series	Size	Watts/Lumens	Color Temp (K)	Options
FLP	22L 2' x 2'	36W3600L 36 Watts/3600 Lumens 45W4250L 45 Watts/4250 Lumens	40K 4000K	EM Battery Backup

## SPECIFICATIONS

Dimensions (in)	23.7 x 23.7 x 3.8
Units/carton	1
Net weight	15 lbs
Environmental Rating	Dry

