


DESCRIPTION

CATALOG: E629C-F-2232-TP	STARTING METHOD: Rapid Start	INPUT VOLTAGE: 120 V~	OCV: 280 V~	FREQUENCY: 60 Hz
BALLAST TYPE: Magnetic Ballast	CLASS: P	TYPE: 1 outdoor	LAMP CONNECTION: Series	SOUND RATED: A
NO PCB'S				

ELECTRICAL CHARACTERISTICS

LAMP TYPE	NUMBER OF LAMPS	LAMP WATTS	MIN. START TEMP. (°F/°C)	INPUT WATTS (Watts)	INPUT CURRENT (Amps)	BALLAST FACTOR	B.E.F.	P.F.	THD %	LAMP CREST FACTOR
FC8T9 with FC12T9	2	22 w/ 33	50/10	40	0.34	0.59	1.475	0.98	12	1.6

PHYSICAL CHARACTERISTICS

		CASE DIMENSIONS					
		UNITS	M1	M2	M3	W	H
		INCHES	1.687	6.00	5.440	2.375	6.560
		TOL(+/-)	0.010	0.010	0.010	0.050	0.050
		MM	43	152	138	60	166
		TOL(+/-)	0.25	0.25	0.25	1.30	1.30
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	10	10	10	10	10		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	254	254	254	254	254		
TOL(+/-)	10	10	10	10	10		

CARTON CHARACTERISTICS


UNITS/CARTON 24	CARTON/LAYER 9	# OF LAYERS 4	UNITS PALLET 864	PIECE WEIGHT 2.8 lbs	CARTON WEIGHT 67.5 lbs	PALLET WEIGHT 2 465 lbs
CARTON PALLET 36	CARTON DIMENSIONS 14" x 10 5/8" x 6 1/8"		PALLET DIMENSIONS 40" x 48" x 7"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 31 1/2"	

MISC.

CARTON LABEL



ELECTRICAL DIAGRAM



PRODUCT LABEL



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.



Lighting and Power Source
2840 Keller Springs Road,
Suite 1102 & 1103
Carrollton, TX 75006 – 4832
Tel: (888) 385-4448
Fax: (972) 418-5858