

RR6

Six-Inch Retrofit Housing

Product Description

The RR6 recessed housing is designed to accommodate all Cree six-inch downlights in retrofit applications. It is rated for use with luminaires that consume low energy, such as the LR6 and CR6, optimizing energy density calculations for easier energy code compliance and LEED certification. The RR6 housing is IC rated, airtight, inherently protected and, when ordered with a GU24 socket, California Title-24 compliant.

Product Specifications

CONSTRUCTION & MATERIALS

Recessed retrofit housing accommodates Cree six-inch LED downlights in ceiling thickness from 0.25" to 1.25".

Gasketed housing enables air-tight fit to effectively isolate housing assembly from conditioned space below.

Suitable for insulated or non-insulated ceilings.

Dimensions: L 12.5" x W 6.625" x H 7.5"

REGULATORY & VOLUNTARY QUALIFICATIONS

cULus Listed

IC air-tight rated, tested in accordance with ASTM E283.

Title-24 compliant when utilized with GU24 socket.

Suitable for damp locations.

Compatible Downlights

RR6
CR6 Series
LR6 Series
LE6 Series

Ordering Information

Example: RR6

Product
RR6 120V, Edison Socket
RR6-GU24 120V, GU24 Socket
RR6-277V 277V, Connector

RR6

