



PERFORMANCE

- Long life: 25,000 hrs (B11); 40,000 hrs (G25)
- +80 CRI
- 120V @ 60Hz

TYPICAL APPLICATIONS

- Task Lighting
- Accent/Display Lighting
- Retail
- Recessed Lighting
- Hospitality
- Residential

FEATURES

- Direct replacement for standard incandescent lamps
- Lasts 30x longer than standard incandescent
- High power LED efficiency
- Dimmable to 5% for design flexibility
- Compatible with a wide array of dimmers
- Comfortable diffuse light
- Instant-On with no warm up, unlike CFLs
- Acceptable for ICAT rated downlights
- Available in 2700K and 3000K

TESTS & CERTIFICATIONS

- 5 year limited warranty
- RoHS Compliant
- UL listed for damp locations
- Non enclosed rated
- No mercury or UV/IR emissions
- IESNA LM-79-08 Report Available
- IESNA LM-63-2002 Photometric File Available

LITESPANTM
LED



DIMENSIONAL DRAWINGS



G25



B11 3W



B11 3.5W



B11 5W



CERTIFIED GREEN

LITESPANLED® DECORATIVE

Dimmable

	ES	LitespanLED® Part #	Description	Lumens	Equiv. to Std. Lamp by Lumen	MOD	MOL	Rated Hours
B11		LEDP-3WB11/827-DIM	B11 3W Dimmable E12 Candelabra Base 2700K UL/CSA	160	25W B10	1.374"	3.78"	25,000
		LEDP-3WB11/830-DIM	B11 3W Dimmable E12 Candelabra Base 3000K UL/CSA	165		1.374"	3.78"	25,000
		LEDP-3.5WB11/827-DIM	B11 3.5W Dimmable E12 Candelabra Base 2700K UL	175		1.374"	3.78"	25,000
		LEDP-3.5WB11/830-DIM	B11 3.5W Dimmable E12 Candelabra Base 3000K UL	180		1.374"	3.78"	25,000
		LEDP-5WB11/827-DIM	B11 5W Dimmable E12 Candelabra Base 2700K UL/C	300	40W B10	1.38"	4.21"	25,000
G25		LEDP-8WG25/827-DIM	G25 8W Dimmable E26 2700K UL/CSA	480	40W G25	3.11"	4.72"	40,000
	★	LEDP-8WG25/830-DIM	G25 8W Dimmable E26 3000K UL/CSA	500		3.11"	4.72"	40,000*

★ ENERGY STAR approved

*ENERGY STAR mandates a maximum published threshold of 25,000 hrs after 6,000 hrs testing, and 40,000 hrs after 10,000 hrs of testing.

