

LITESPAN[®] LAMPS

LED replacement lamps



energy efficient • long life • wide selection

eiko.com

EIKO [®]
CERTIFIED GREEN

Every industry thrives on new and forward thinking technology. While LEDs aren't new, in recent years their performance and reliability have improved to make them a more viable option for general and task-oriented lighting. Eiko's extended line of **LITESPANLED®** Linears and Replacement Lamps truly represent the next generation in lighting by saving you time, money, and energy through the use of quality Cree chips for long life, superior lumen and color maintenance. They also feature instant, flicker-free start-up and no off-state power draw.



PAR & MR



Linear



Decorative



R/BR



A19

LITESPANLED® PAR & MR Lamps

Ordering Code	Watts	Volts	Shape	MOL mm	MOD mm	Lumens	Color Temp	CRI	Beam Angle	Avg. Life Hours
LEDP-6WPAR16/FL/830-DIM	6	120	PAR16	83	50	370	3000	>80	40	35,000
LEDP-6WPAR16/FL/841-DIM	6	120	PAR16	83	50	385	4100	>80	40	35,000
LEDP-7WPAR20/FL/841-DIM	7	120	PAR20	85	63	400	4100	>80	40	40,000
LEDP-7WPAR20/NFL/827-DIM	7	120	PAR20	85	63	320	2700	>80	25	40,000
LEDP-7WPAR20/NFL/841-DIM	7	120	PAR20	85	63	350	4100	>80	25	40,000
LEDP-8WPAR20/FL/827-DIM	8	120	PAR20	87	63	365	2700	>80	40	35,000
LEDP-8WPAR20/FL/830-DIM	8	120	PAR20	87	63	380	3000	>80	40	35,000
LEDP-8WPAR20/FL/841-DIM	8	120	PAR20	87	63	395	4100	>80	40	35,000
LEDP-8WPAR20/NFL/827-DIM	8	120	PAR20	87	63	365	2700	>80	25	35,000
LEDP-8WPAR20/NFL/830-DIM	8	120	PAR20	87	63	380	3000	>80	25	35,000
LEDP-8WPAR20/NFL/841-DIM	8	120	PAR20	87	63	395	4100	>80	25	35,000
LEDP-13WPAR30/FL/827-DIM	13	120	PAR30	113	95	680	2700	>80	40	35,000
LEDP-13WPAR30/FL/830-DIM	13	120	PAR30	113	95	700	3000	>80	40	25,000
LEDP-13WPAR30/FL/841-DIM	13	120	PAR30	113	95	730	4100	>80	40	35,000
LEDP-13WPAR30/NFL/827-DIM	13	120	PAR30	113	95	680	2700	>80	25	35,000
LEDP-13WPAR30/NFL/830-DIM	13	120	PAR30	113	95	700	3000	>80	25	35,000
LEDP-13WPAR30/NFL/841-DIM	13	120	PAR30	113	95	730	4100	>80	25	35,000
LEDP-15WPAR30/FL/830-DIM	15	120	PAR30	118	95	800	3000	>80	40	25,000
LEDP-15WPAR30/NFL/827-DIM	15	120	PAR30	118	95	730	2700	>80	25	25,000
LEDP-15WPAR30/NFL/830-DIM	15	120	PAR30	118	95	750	3000	>80	25	25,000
LEDP-15WPAR30/NFL/841-DIM	15	120	PAR30	118	95	760	4100	>80	25	25,000
LEDP-15WPAR30SN/FL/830-DIM	15	120	PAR30SN	95	95	800	3000	>80	40	25,000
LEDP-15WPAR30SN/FL/841-DIM	15	120	PAR30SN	95	95	750	4100	>80	40	40,000
LEDP-15WPAR30SN/NFL/830-DIM	15	120	PAR30SN	95	95	750	3000	>80	25	25,000
LEDP-15WPAR30SN/NFL/841-DIM	15	120	PAR30SN	95	95	750	4100	>80	25	40,000
LEDP-20WPAR38/FL/827-DIM	20	120	PAR38	130	120	1050	2700	>80	25	25,000
LEDP-20WPAR38/NFL/830-DIM	20	120	PAR38	130	120	1100	3000	>80	25	25,000
LEDP-20WPAR38/NFL/841-DIM	20	120	PAR38	130	120	1250	4100	>80	25	25,000
LEDP-20WPAR38/FL/827-DIM	20	120	PAR38	130	120	1150	2700	>80	40	25,000
LEDP-20WPAR38/FL/830-DIM	20	120	PAR38	130	120	1200	3000	>80	40	35,000
LEDP-20WPAR38/FL/841-DIM	20	120	PAR38	130	120	1250	4100	>80	40	25,000
LEDP-6WGU10/830-DIM	6	120	MR16	57	50	320	3000	>80	38	40,000
LEDP-6WGU10/841-DIM	6	120	MR16	79	50	385	4100	80	40	35,000
LEDP-6WMR16/827-DIM	6	12	MR16	61	50	340	2700	>80	40	35,000
LEDP-6WMR16/830-DIM	6	12	MR16	50	50	320	3000	>80	38	40,000

EiKO USA: 23220 W. 84th Street, Shawnee, KS 66227 • Ph: 1.800.852.2217 • Fax: 1.800.492.8975

EiKO Canada: 81 King Street, Barrie, ON L4N 6B5, Canada • Ph: 1.888.410.8151 • Fax: 1.888.705.1335

LITESPANLED® Linear Lamps

Ordering Code	Watts	Volts	Shape	MOL mm	MOD mm	Lumens	Color Temp	CRI	Beam Angle	Avg. Life Hours
LEDP-9T8/24/41K	9	120-277VAC	T-8	605	28	850	4100	>70	114	50,000
LEDP-9T8/24/41K	9	120-277VAC	T-8	605	28	850	4100	>70	114	50,000
LEDP-14T8/36/41K	14	120-277VAC	T-8	908	28	1100	4100	>70	114	50,000
LEDP-14T8/36/50K	14	120-277VAC	T-8	908	28	1100	5000	>70	114	50,000
LEDP-18T8/48/30K	18	120-277VAC	T-8	1213	28	1700	3000	>70	114	50,000
LEDP-18T8/48/41K	18	120-277VAC	T-8	1213	28	1700	4100	>70	114	50,000
LEDP-18T8/48/50K	18	120-277VAC	T-8	1213	28	1700	5000	>70	114	50,000
LEDP-22T8/60/41K	22	120-277VAC	T-8	1513	28	2100	4100	>70	114	50,000
LEDP-22T8/60/50K	22	120-277VAC	T-8	1513	28	2100	5000	>70	114	50,000
LEDP-24T8/72/41K	24	120-277VAC	T-8	1813	28	2300	4100	>70	114	50,000
LEDP-24T8/72/50K	24	120-277VAC	T-8	1813	28	2300	5000	>70	114	50,000
LEDP-18T8U6/41K	18	120-277VAC	T-8	560	28	1700	4100	>70	-	50,000
LEDP-18T8U6/50K	18	120-277VAC	T-8	560	28	1700	5000	>70	-	50,000

LITESPANLED® Decorative Lamps

Ordering Code	Watts	Volts	Shape	MOL mm	MOD mm	Lumens	Color Temp	CRI	Beam Angle	Avg. Life Hours
LEDP-3.5WB11/827-DIM	5	120	B11	96	34.9	175	2700	>80	>300	25,000
LEDP-3.5WB11/830-DIM	5	120	B11	96	34.9	180	2700	>80	>300	25,000
LEDP-5WB11/827-DIM	5	120	B11	107	35	300	2700	>80	>300	25,000
LEDP-5WB11/830-DIM	5	120	B11	107	35	300	3000	>80	>300	25,000
LEDP-8WG25/827-DIM	8	120	G25	120	79	480	2700	>80	120	40,000
LEDP-8WG25/830-DIM	8	120	G25	120	79	500	3000	>80	120	40,000

LITESPANLED® BR/R Lamps

Ordering Code	Watts	Volts	Shape	MOL mm	MOD mm	Lumens	Color Temp	CRI	Beam Angle	Avg. Life Hours
LEDP-8WR20/827-DIM3	8	120	R20	100	63	500	2700	80	106	25,000
LEDP-8WR20/830-DIM3	8	120	R20	100	63	520	3000	80	106	35,000
LEDP-8WR20/841-DIM3	8	120	R20	100	63	540	4100	80	106	35,000
LEDP-11WR30/827-DIM	11	120	R30	130	95	730	2700	>80	108	35,000
LEDP-11WR30/830-DIM	11	120	R30	130	95	750	3000	>80	108	35,000
LEDP-11WR30/GU24/827-DIM	11	120	R30	130	95	730	2700	>80	108	35,000
LEDP-11WR30/GU24/830-DIM	11	120	R30	130	95	750	2700	>80	108	35,000
LEDP-13WR40/827-DIM3	13	120	R40	164	127	850	2700	80	105	25,000
LEDP-13WR40/830-DIM3	13	120	R40	164	127	880	3000	80	105	35,000
LEDP-13WR40/841-DIM3	13	120	R40	164	127	920	4100	80	105	35,000
LEDP-18WR40/827-DIM3	18	120	R40	164	127	1200	2700	80	105	25,000
LEDP-18WR40/830-DIM3	18	120	R40	164	127	1230	3000	80	105	35,000
LEDP-18WR40/841-DIM3	18	120	R40	164	127	1280	4100	80	105	35,000

LITESPANLED® A19 Lamps

Ordering Code	Watts	Volts	Shape	MOL mm	MOD mm	Lumens	Color Temp	CRI	Beam Angle	Avg. Life Hours
LEDP-8WA19/827-DIM3	8	120	A19	108	58	435	2700	>80	>300	25,000
LEDP-8WA19/830-DIM3	8	120	A19	108	58	450	3000	>80	>300	25,000
LEDP-8WA19/841-DIM3	8	120	A19	108	58	470	4100	>80	>300	25,000
LEDP-8WA19/850-DIM3	8	120	A19	108	58	510	5000	80	116	25,000
LEDP-10WA19/827-DIM3	10	120	A19	112	60	800	2700	80	120	25,000
LEDP-10WA19/830-DIM3	10	120	A19	112	60	830	3000	80	120	25,000
LEDP-10WA19/841-DIM3	10	120	A19	112	60	860	4100	80	120	25,000
LEDP-12WA19/827-DIM	12	120	A19	118	60	800	2700	>80	>300	25,000
LEDP-12WA19/830-DIM	12	120	A19	118	60	800	3000	>80	>300	25,000
LEDP-12WA19/841-DIM	12	120	A19	112	60	860	4100	80	335	25,000



PAR & MR

- **PAR16**
- **PAR20**
- **PAR30**
- **PAR38**
- **MR16**
- **GU10**

- Direct replacement for halogen PAR lamps
- Dimmable to 5% for design flexibility
- Compatible with a wide array of dimmers

- **2' Linear**
- **3' Linear**
- **4' Linear**
- **5' Linear**
- **6' Linear**
- **6' U-Bend**

- Available in a variety of sizes and wattages
- Reduces power consumption and energy costs
- 50,000 hour long life



Linear



Decorative

- **B11 Blunt Tip Candle**
- **G25 Globe**

- Direct replacement for incandescent lamps
- Dimmable to 5% for design flexibility
- Compatible with a wide array of dimmers

- **R20**
- **R30**
- **R30GU24**
- **R40**

- Direct replacement for incandescent R lamps
- Dimmable to 5% for design flexibility
- Compatible with a wide array of dimmers



R/BR



A19

- **8W A19**
- **10W A19**
- **12W A19**

- Direct replacement for incandescent A lamps
- Lasts 30x longer than incandescent
- High power LED efficiency

watch



like



follow



EiKO USA: 23220 W. 84th Street, Shawnee, KS 66227 • Ph: 1.800.852.2217 • Fax: 1.800.492.8975
EiKO Canada: 81 King Street, Barrie, ON L4N 6B5, Canada • Ph: 1.888.410.8151 • Fax: 1.888.705.1335