

**Non Dimmable
Designer Elite
LED PAR
Lamps**

14W ELITE DESIGNER NON DIMMABLE PAR30 (REPLACES 90W)



Item Number	ENERGY STAR®	Item Description	Voltage	Lamp Watts	Lumens	Lumens Per Watt	*CBCP	Beam Angle	CCT	CRI	STK/MTO	Case Quantity
LED14P3024KFL		14W Smooth PAR30 - 2400K 40 Degree	120	14	1050	75.0	1758	40	2400K	82	MTO	12
LED14P3024KNFL		14W Smooth PAR30 - 2400K 25 Degree	120	14	1050	75.0	3891	25	2400K	82	MTO	12
LED14P3024KSP		14W Smooth PAR30 - 2400K 15 Degree	120	14	1050	75.0	8230	15	2400K	82	MTO	12
LED14P3027KFL	★	14W Smooth PAR30 - 2700K 40 Degree	120	14	1050	75.0	1758	40	2700K	82	STK	12
LED14P3027KNFL		14W Smooth PAR30 - 2700K 25 Degree	120	14	1050	75.0	3891	25	2700K	82	STK	12
LED14P3027KSP	★	14W Smooth PAR30 - 2700K 15 Degree	120	14	1050	75.0	8230	15	2700K	82	MTO	12
LED14P3030KFL	★	14W Smooth PAR30 - 3000K 40 Degree	120	14	1100	78.6	1758	40	3000K	82	STK	12
LED14P3030KNFL	★	14W Smooth PAR30 - 3000K 25 Degree	120	14	1100	78.6	3891	25	3000K	82	STK	12
LED14P3030KSP	★	14W Smooth PAR30 - 3000K 15 Degree	120	14	1100	78.6	8230	15	3000K	82	MTO	12
LED14P3035KFL	★	14W Smooth PAR30 - 3500K 40 Degree	120	14	1125	80.4	1758	40	3500K	82	MTO	12
LED14P3035KNFL	★	14W Smooth PAR30 - 3500K 25 Degree	120	14	1125	80.4	3891	25	3500K	82	MTO	12
LED14P3035KSP	★	14W Smooth PAR30 - 3500K 15 Degree	120	14	1125	80.4	8230	15	3500K	82	MTO	12
LED14P3041KFL		14W Smooth PAR30 - 4100K 40 Degree	120	14	1150	82.1	1758	40	4100K	82	MTO	12
LED14P3041KNFL	★	14W Smooth PAR30 - 4100K 25 Degree	120	14	1150	82.1	3891	25	4100K	82	MTO	12
LED14P3041KSP	★	14W Smooth PAR30 - 4100K 15 Degree	120	14	1150	82.1	8230	15	4100K	82	MTO	12
LED14P3050KFL		14W Smooth PAR30 - 5000K 40 Degree	120	14	1150	82.1	1758	40	5000K	82	MTO	12
LED14P3050KNFL		14W Smooth PAR30 - 5000K 25 Degree	120	14	1150	82.1	3891	25	5000K	82	MTO	12
LED14P3050KSP		14W Smooth PAR30 - 5000K 15 Degree	120	14	1150	82.1	8230	15	5000K	82	MTO	12

12W ELITE DESIGNER NON DIMMABLE PAR30 (REPLACES 75W)



LED12P3024KFL		12W Smooth PAR30 - 2400K 40 Degree	120	12	800	66.7	1315	40	2400K	82	MTO	12
LED12P3024KNFL		12W Smooth PAR30 - 2400K 25 Degree	120	12	800	66.7	2910	25	2400K	82	MTO	12
LED12P3024KSP		12W Smooth PAR30 - 2400K 15 Degree	120	12	800	66.7	6155	15	2400K	82	MTO	12
LED12P3027KFL	★	12W Smooth PAR30 - 2700K 40 Degree	120	12	800	66.7	1315	40	2700K	82	STK	12
LED12P3027KNFL	★	12W Smooth PAR30 - 2700K 25 Degree	120	12	800	66.7	2910	25	2700K	82	STK	12
LED12P3027KSP		12W Smooth PAR30 - 2700K 15 Degree	120	12	800	66.7	6155	15	2700K	82	MTO	12
LED12P3030KFL	★	12W Smooth PAR30 - 3000K 40 Degree	120	12	825	68.8	1315	40	3000K	82	STK	12
LED12P3030KNFL	★	12W Smooth PAR30 - 3000K 25 Degree	120	12	825	68.8	2910	25	3000K	82	STK	12
LED12P3030KSP	★	12W Smooth PAR30 - 3000K 15 Degree	120	12	825	68.8	6155	15	3000K	82	MTO	12
LED12P3035KFL	★	12W Smooth PAR30 - 3500K 40 Degree	120	12	850	70.8	1315	40	3500K	82	MTO	12
LED12P3035KNFL	★	12W Smooth PAR30 - 3500K 25 Degree	120	12	850	70.8	2910	25	3500K	82	MTO	12
LED12P3035KSP	★	12W Smooth PAR30 - 3500K 15 Degree	120	12	850	70.8	6155	15	3500K	82	MTO	12
LED12P3041KFL	★	12W Smooth PAR30 - 4100K 40 Degree	120	12	875	72.9	1315	40	4100K	82	MTO	12
LED12P3041KNFL		12W Smooth PAR30 - 4100K 25 Degree	120	12	875	72.9	2910	25	4100K	82	MTO	12
LED12P3041KSP	★	12W Smooth PAR30 - 4100K 15 Degree	120	12	875	72.9	6155	15	4100K	82	MTO	12
LED12P3050KFL		12W Smooth PAR30 - 5000K 40 Degree	120	12	875	72.9	1315	40	5000K	82	MTO	12
LED12P3050KNFL		12W Smooth PAR30 - 5000K 25 Degree	120	12	875	72.9	2910	25	5000K	82	MTO	12
LED12P3050KSP		12W Smooth PAR30 - 5000K 15 Degree	120	12	875	72.9	6155	15	5000K	82	MTO	12

LED Lamps

TCP CATALOG
800.324.1496 | tcp.com

★ ENERGY STAR® Rated (at time of print)



*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.

Item Number	ENERGY STAR®	Item Description	Voltage	Lamp Watts	Lumens	Lumens Per Watt	*CBCP	Beam Angle	CCT	CRI	STK/MTO	Case Quantity
-------------	--------------	------------------	---------	------------	--------	-----------------	-------	------------	-----	-----	---------	---------------

Non Dimmable
Designer Elite
LED PAR
Lamps

12W ELITE DESIGNER NON DIMMABLE PAR30 SHORT NECK (REPLACES 75W)

LED12P30S24KFL		12W Smooth PAR30 SN - 2400K 40 Degree	120	12	800	66.7	1315	40	2400K	82	MTO	12
LED12P30S24KNFL		12W Smooth PAR30 SN - 2400K 25 Degree	120	12	800	66.7	2910	25	2400K	82	MTO	12
LED12P30S24KSP		12W Smooth PAR30 SN - 2400K 15 Degree	120	12	800	66.7	6155	15	2400K	82	MTO	12
LED12P30S27KFL		12W Smooth PAR30 SN - 2700K 40 Degree	120	12	800	66.7	1315	40	2700K	82	STK	12
LED12P30S27KNFL	★	12W Smooth PAR30 SN - 2700K 25 Degree	120	12	800	66.7	2910	25	2700K	82	STK	12
LED12P30S27KSP		12W Smooth PAR30 SN - 2700K 15 Degree	120	12	800	66.7	6155	15	2700K	82	MTO	12
LED12P30S30KFL		12W Smooth PAR30 SN - 3000K 40 Degree	120	12	825	68.8	1315	40	3000K	82	STK	12
LED12P30S30KNFL		12W Smooth PAR30 SN - 3000K 25 Degree	120	12	825	68.8	2910	25	3000K	82	STK	12
LED12P30S30KSP		12W Smooth PAR30 SN - 3000K 15 Degree	120	12	825	68.8	6155	15	3000K	82	MTO	12
LED12P30S35KFL		12W Smooth PAR30 SN - 3500K 40 Degree	120	12	850	70.8	1315	40	3500K	82	MTO	12
LED12P30S35KNFL		12W Smooth PAR30 SN - 3500K 25 Degree	120	12	850	70.8	2910	25	3500K	82	MTO	12
LED12P30S35KSP		12W Smooth PAR30 SN - 3500K 15 Degree	120	12	850	70.8	6155	15	3500K	82	MTO	12
LED12P30S41KFL		12W Smooth PAR30 SN - 4100K 40 Degree	120	12	875	72.9	1315	40	4100K	82	MTO	12
LED12P30S41KNFL		12W Smooth PAR30 SN - 4100K 25 Degree	120	12	875	72.9	2910	25	4100K	82	MTO	12
LED12P30S41KSP		12W Smooth PAR30 SN - 4100K 15 Degree	120	12	875	72.9	6155	15	4100K	82	MTO	12
LED12P30S50KFL		12W Smooth PAR30 SN - 5000K 40 Degree	120	12	875	72.9	1315	40	5000K	82	MTO	12
LED12P30S50KNFL		12W Smooth PAR30 SN - 5000K 25 Degree	120	12	875	72.9	2910	25	5000K	82	MTO	12
LED12P30S50KSP		12W Smooth PAR30 SN - 5000K 15 Degree	120	12	875	72.9	6155	15	5000K	82	MTO	12



10W ELITE DESIGNER NON DIMMABLE PAR30 SHORT NECK (REPLACES 60W)

LED10P30S24KFL		10W Smooth PAR30 SN - 2400K 40 Degree	120	10	600	60.0	957	40	2400K	82	MTO	12
LED10P30S24KNFL		10W Smooth PAR30 SN - 2400K 25 Degree	120	10	600	60.0	2118	25	2400K	82	MTO	12
LED10P30S24KSP		10W Smooth PAR30 SN - 2400K 15 Degree	120	10	600	60.0	4480	15	2400K	82	MTO	12
LED10P30S27KFL	★	10W Smooth PAR30 SN - 2700K 40 Degree	120	10	600	60.0	957	40	2700K	82	STK	12
LED10P30S27KNFL	★	10W Smooth PAR30 SN - 2700K 25 Degree	120	10	600	60.0	2118	25	2700K	82	STK	12
LED10P30S27KSP		10W Smooth PAR30 SN - 2700K 15 Degree	120	10	600	60.0	4480	15	2700K	82	MTO	12
LED10P30S30KFL		10W Smooth PAR30 SN - 3000K 40 Degree	120	10	650	65.0	957	40	3000K	82	STK	12
LED10P30S30KNFL		10W Smooth PAR30 SN - 3000K 25 Degree	120	10	650	65.0	2118	25	3000K	82	STK	12
LED10P30S30KSP		10W Smooth PAR30 SN - 3000K 15 Degree	120	10	650	65.0	4480	15	3000K	82	MTO	12
LED10P30S35KFL		10W Smooth PAR30 SN - 3500K 40 Degree	120	10	675	67.5	957	40	3500K	82	MTO	12
LED10P30S35KNFL		10W Smooth PAR30 SN - 3500K 25 Degree	120	10	675	67.5	2118	25	3500K	82	MTO	12
LED10P30S35KSP		10W Smooth PAR30 SN - 3500K 15 Degree	120	10	675	67.5	4480	15	3500K	82	MTO	12
LED10P30S41KFL		10W Smooth PAR30 SN - 4100K 40 Degree	120	10	700	70.0	957	40	4100K	82	MTO	12
LED10P30S41KNFL		10W Smooth PAR30 SN - 4100K 25 Degree	120	10	700	70.0	2118	25	4100K	82	MTO	12
LED10P30S41KSP		10W Smooth PAR30 SN - 4100K 15 Degree	120	10	700	70.0	4480	15	4100K	82	MTO	12
LED10P30S50KFL		10W Smooth PAR30 SN - 5000K 40 Degree	120	10	700	70.0	957	40	5000K	82	MTO	12
LED10P30S50KNFL		10W Smooth PAR30 SN - 5000K 25 Degree	120	10	700	70.0	2118	25	5000K	82	MTO	12
LED10P30S50KSP		10W Smooth PAR30 SN - 5000K 15 Degree	120	10	700	70.0	4480	15	5000K	82	MTO	12

★ ENERGY STAR® Rated (at time of print)



*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.