

Non Dimmable

Non Dimmable Designer Elite LED PAR Lamps

Item Number	ENERGY STAR® Item Description	Voltage	Lamp Watts	Lumens	Lumens Per Watt	*CBCP	Beam Angle	CCT	CRI	STK/MTO	Case Quantity
17W ELITE DESIGNER NON DIMMABLE PAR38 (REPLACES 120W)											
LED17P3824KFL	17W Smooth PAR38 - 2400K 40 Degree	120	17	1200	70.6	2231	40	2400K	82	MTO	12
LED17P3824KNFL	17W Smooth PAR38 - 2400K 25 Degree	120	17	1200	70.6	5382	25	2400K	82	MTO	12
LED17P3824KSP	17W Smooth PAR38 - 2400K 15 Degree	120	17	1200	70.6	12059	15	2400K	82	MTO	12
LED17P3827KFL	17W Smooth PAR38 - 2700K 40 Degree	120	17	1200	70.6	2231	40	2700K	82	STK	12
LED17P3827KNFL	★ 17W Smooth PAR38 - 2700K 25 Degree	120	17	1200	70.6	5382	25	2700K	82	STK	12
LED17P3827KSP	17W Smooth PAR38 - 2700K 15 Degree	120	17	1200	70.6	12059	15	2700K	82	MTO	12
LED17P3830KFL	★ 17W Smooth PAR38 - 3000K 40 Degree	120	17	1250	73.5	2231	40	3000K	82	STK	12
LED17P3830KNFL	★ 17W Smooth PAR38 - 3000K 25 Degree	120	17	1250	73.5	5382	25	3000K	82	STK	12
LED17P3830KSP	17W Smooth PAR38 - 3000K 15 Degree	120	17	1250	73.5	12059	15	3000K	82	MTO	12
LED17P3835KFL	★ 17W Smooth PAR38 - 3500K 40 Degree	120	17	1275	75.0	2231	40	3500K	82	MTO	12
LED17P3835KNFL	★ 17W Smooth PAR38 - 3500K 25 Degree	120	17	1275	75.0	5382	25	3500K	82	MTO	12
LED17P3835KSP	17W Smooth PAR38 - 3500K 15 Degree	120	17	1275	75.0	12059	15	3500K	82	MTO	12
LED17P3841KFL	★ 17W Smooth PAR38 - 4100K 40 Degree	120	17	1300	76.5	2231	40	4100K	82	MTO	12
LED17P3841KNFL	17W Smooth PAR38 - 4100K 25 Degree	120	17	1300	76.5	5382	25	4100K	82	MTO	12
LED17P3841KSP	★ 17W Smooth PAR38 - 4100K 15 Degree	120	17	1300	76.5	12059	15	4100K	82	MTO	12
LED17P3850KFL	17W Smooth PAR38 - 5000K 40 Degree	120	17	1300	76.5	2231	40	5000K	82	MTO	12
LED17P3850KNFL	17W Smooth PAR38 - 5000K 25 Degree	120	17	1300	76.5	5382	25	5000K	82	MTO	12
LED17P3850KSP	17W Smooth PAR38 - 5000K 15 Degree	120	17	1300	76.5	12059	15	5000K	82	MTO	12
14W ELITE DESIGNER NON DIMMABLE PAR38 (REPLACES 90W)											
LED14P3824KFL	14W Smooth PAR38 - 2400K 40 Degree	120	14	1050	75.0	1533	40	2400K	82	MTO	12
LED14P3824KNFL	14W Smooth PAR38 - 2400K 25 Degree	120	14	1050	75.0	3697	25	2400K	82	MTO	12
LED14P3824KSP	14W Smooth PAR38 - 2400K 15 Degree	120	14	1050	75.0	8284	15	2400K	82	MTO	12
LED14P3827KFL	14W Smooth PAR38 - 2700K 40 Degree	120	14	1050	75.0	1533	40	2700K	82	STK	12
LED14P3827KNFL	★ 14W Smooth PAR38 - 2700K 25 Degree	120	14	1050	75.0	3697	25	2700K	82	STK	12
LED14P3827KSP	★ 14W Smooth PAR38 - 2700K 15 Degree	120	14	1050	75.0	8284	15	2700K	82	MTO	12
LED14P3830KFL	★ 14W Smooth PAR38 - 3000K 40 Degree	120	14	1100	78.6	1533	40	3000K	82	STK	12
LED14P3830KNFL	★ 14W Smooth PAR38 - 3000K 25 Degree	120	14	1100	78.6	3697	25	3000K	82	STK	12
LED14P3830KSP	★ 14W Smooth PAR38 - 3000K 15 Degree	120	14	1100	78.6	8284	15	3000K	82	MTO	12
LED14P3835KFL	★ 14W Smooth PAR38 - 3500K 40 Degree	120	14	1125	80.4	1533	40	3500K	82	MTO	12
LED14P3835KNFL	★ 14W Smooth PAR38 - 3500K 25 Degree	120	14	1125	80.4	3697	25	3500K	82	MTO	12
LED14P3835KSP	★ 14W Smooth PAR38 - 3500K 15 Degree	120	14	1125	80.4	8284	15	3500K	82	MTO	12
LED14P3841KFL	★ 14W Smooth PAR38 - 4100K 40 Degree	120	14	1150	82.1	1533	40	4100K	82	MTO	12
LED14P3841KNFL	14W Smooth PAR38 - 4100K 25 Degree	120	14	1150	82.1	3697	25	4100K	82	MTO	12
LED14P3841KSP	★ 14W Smooth PAR38 - 4100K 15 Degree	120	14	1150	82.1	8284	15	4100K	82	MTO	12
LED14P3850KFL	14W Smooth PAR38 - 5000K 40 Degree	120	14	1150	82.1	1533	40	5000K	82	MTO	12
LED14P3850KNFL	14W Smooth PAR38 - 4100K 25 Degree	120	14	1150	82.1	3697	25	5000K	82	MTO	12
LED14P3850KSP	14W Smooth PAR38 - 4100K 15 Degree	120	14	1150	82.1	8284	15	5000K	82	MTO	12



★ ENERGY STAR® Rated (at time of print)



*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.

LED Lamps

TCP CATALOG
800.324.1496 | tcp.com