



Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	†Wattage Equivalency	*Rated Life - Hours L70	Dimmable	††ENERGY STAR®	‡Location Rating	Additional Information
------------	-----------	-------	------------	-------------	-------	----------	----------	----------------	------	--------------------	-----	----------------------	-------------------------	----------	----------------	------------------	------------------------

Directional Lamps (PAR) (continued)

Compact PAR30 (Halogen replacement info below is based on ENERGY STAR® requirements for center beam candlepower)

PAR30	MED	10	61922	LED10DP30S830/20	120	6	3.75	500	3720	3000	80	60W	50,000	▲	★	Damp	Accent, 20° beam, Silver, 60-w Repl.
		10	61923	LED10DP30S827/20	120	6	3.75	450	3450	2700	80	55W	50,000	▲	★	Damp	Accent, 20° beam, Silver, 55-w Repl.
		10	64326	LED10DP30W827/20	120	6	3.75	450	3450	2700	80	55W	50,000	▲	★	Damp	Accent, 20° beam, White, 55-w Repl.
		10	63026	LED10DP3/FL/TP	120	3	3.75	450	1240	2700	80	55W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 55-w Repl.
		12	65135	LED12DP30S830/20	120	6	3.75	750	4600	3000	84	75W	25,000	▲	★	Damp	Accent, 20° beam, Silver, 75-w Repl.
		12	65136	LED12DP30S830/35	120	6	3.75	750	2050	3000	84	80W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 80-w Repl.
		12	65137	LED12DP30S827/20	120	6	3.75	740	4400	2700	83	75W	25,000	▲	★	Damp	Accent, 20° beam, Silver, 75-w Repl.
		12	65138	LED12DP30S827/35	120	6	3.75	740	2000	2700	83	80W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 80-w Repl.
		12	65133	LED12DP30S/FL/TP	120	3	3.75	740	2000	2700	83	80W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 80-w Repl.
		12	65985	LED12DP30S827/25	120	6	3.75	740	3200	2700	83	75W	25,000	▲	★	Damp	Accent, 25° beam, Silver, 75-w Repl.
		12	65986	LED12DP30W827/25	120	6	3.75	740	3200	2700	83	75W	25,000	▲	★	Damp	Accent, 25° beam, White, 75-w Repl.
		12	65987	LED12DP30B827/25	120	6	3.75	740	3200	2700	83	75W	25,000	▲	★	Damp	Accent, 25° beam, Black, 75-w Repl.
		12	67256	LED12DP30S840/20	120	6	3.75	840	5300	4000	85	90W	25,000	▲	★	Damp	Accent, 25° beam, Silver, 90-w Repl.
		12	67257	LED12DP30S840/35	120	6	3.75	840	2200	4000	85	90W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 90-w Repl.
		12	94215	LED12DP302W83020	120	6	3.66	950	7300	3000	84	85W	25,000	▲	★	Damp	Accent, 20° beam, White
		12	94216	LED12DP302W83035	120	6	3.66	950	2700	3000	84	85W	25,000	▲	★	Damp	Accent, 35° beam, White
		12	94219	LED12DP302W82720	120	6	3.66	850	6600	2700	84	85W	25,000	▲	★	Damp	Accent, 20° beam, White
		12	94220	LED12DP302W82735	120	6	3.66	850	2300	2700	84	85W	25,000	▲	★	Damp	Accent, 35° beam, White
	12	89988	LED12DP302/FL/TP	120	3	3.66	850	2300	2700	84	75W	25,000	▲	★	Damp	Accent, 35° beam, White	

Compact PAR30 Long Neck (Halogen replacement info below is based on ENERGY STAR® requirements for center beam candlepower)

PAR30L	MED	10	61924	LED10DP3LS830/20	120	6	4.75	500	3720	3000	80	60W	50,000	▲	★	Damp	Accent, 20° beam, Silver, 60-w Repl.
		10	61925	LED10DP3LS827/20	120	6	4.75	450	3450	2700	80	55W	50,000	▲	★	Damp	Accent, 20° beam, Silver, 55-w Repl.
		10	68014	LED10DP3LS827/35	120	6	4.75	450	1240	2700	80	55W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 55-w Repl.
		10	63027	LED10DP3L/FL/TP	120	3	4.75	450	1240	2700	80	55W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 55-w Repl.
		12	65140	LED12DP3LS830/35	120	6	4.75	750	2050	3000	84	80W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 80-w Repl.
		12	65141	LED12DP3LS827/20	120	6	4.75	740	4400	2700	83	75W	25,000	▲	★	Damp	Accent, 20° beam, Silver, 75-w Repl.
		12	65142	LED12DP3LS827/35	120	6	4.75	740	2000	2700	83	80W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 80-w Repl.
		12	65134	LED12DP3LS/FL/TP	120	3	4.75	740	2000	2700	83	80W	25,000	▲	★	Damp	Accent, 35° beam, Silver, 80-w Repl.
		12	94212	LED12DP3L2W83020	120	6	4.61	950	7300	3000	84	85W	25,000	▲	★	Damp	Accent, 20° beam, White
		12	94214	LED12DP3L2W83035	120	6	4.61	950	2700	3000	84	85W	25,000	▲	★	Damp	Accent, 35° beam, White
		12	94218	LED12DP3L2W82735	120	6	4.61	850	2300	2700	84	85W	25,000	▲	★	Damp	Accent, 35° beam, White
		12	11306	LED12DP3L2W83535	120	6	4.61	950	2700	3500	84	85W	25,000	▲	★	Damp	Accent, 35° beam, White
		12	89989	LED12DP3L2/FL/TP	120	3	4.61	850	2300	2700	84	75W	25,000	▲	★	Damp	Accent, 35° beam, White
		12	22233	LED12DP3L2FLSKTP	120	3	4.61	1050	3000	5000	84	75W	25,000	▲	★	Damp	Accent, 35° beam, White

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen rating (L70).
 ** Minimum order quantity = 6
 † Incandescent or halogen wattage equivalencies based on Energy Star guidelines using lumens or CBCP according to lamp type
 †† Energy Star status: Certified as meeting Energy Star guidelines.
 ‡ UL 1993 Environmental Requirements for LED Lamps, see page 6-2.
 Note: Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

For the most up-to-date product information, see www.gelighting.com. To convert inches to millimeters, multiply by 25.4.
 All footnote references found at the end of this section.