



Commercial Products &amp; Solutions


 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 97594**97594 – F13DBX/827/ECO4P**

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



 High Color Rendering  
Energy Savings
**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Plug-In
Bulb	T4
Base	G24q-1
Wattage	13
Rated Life	12000 hrs/20000 hrs
Starting Temperature (MIN)	0 °C (32 °F)
Cathode Resistance	10.500 Ohm
LEED-EB MR Credit	442 picograms Hg per mean lumen hour
Additional Info	Dimmable with appropriate dimming ballast., End of Life Protection (EOL), TCLP compliant
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

Bulb



Base

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)[Disposal Policies & Recycling Information](#)**PHOTOMETRIC CHARACTERISTICS**


Mean Lumens	755
Color Temperature	2700 K
Color Rendering Index (CRI)	82

**ELECTRICAL CHARACTERISTICS**

Current (max)	5.2500 A
Open Circuit Voltage (after preheating) (MAX)	190 V
Open Circuit Voltage Across Starter (MIN)	198 V
Lamp Current	0.175 A
Preheat Voltage (MIN)	4 V

**DIMENSIONS**

Maximum Overall Length (MOL)	5.0000 in (127 mm)
Nominal Length	5.000 in (127 mm)
Bulb Diameter (DIA)	0.406 in (10.3 mm)

**GRAPHS & CHARTS****Spectral Power Distribution**

**PRODUCT INFORMATION**

Product Code	97594
Description	F13DBX/827/ECO4P
ANSI Code	60501-IEC-2513-2
Standard Package	BUNDLE
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168975940

**COMPATIBLE GE BALLASTS**

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
<a href="#">80669</a>	C213UNVBE-IP	1	98.0	1.0
<a href="#">71430</a>	GEC213-MVPS-3W	1	96.0	1.0
<a href="#">71428</a>	GEC213-MVPS-BES	1	96.0	1.0
<a href="#">71429</a>	GEC213-MVPS-SE	1	96.0	1.0

** CAUTIONS & WARNINGS**

[See list of cautions & warnings.](#)

**NOTES**

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)  
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009