


# 16649 - F18BX/SPX30 10PK

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse







## **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

### **GENERAL CHARACTERISTICS**

Lamp Type Compact Fluorescent - Plug-

In

Bulb 1

Base 4-Pin (2G11)

Equivalent Wattage (NOM) 65.0 W

Rated Life (NOM) 10000.0 h

Starting Temperature (MIN) -4.0 °C

Mercury Content (NOM) 4.0 mg

Picograms of Mercury (NOM) 370.3704 pg

Primary Application Facilities;Retail

Facilities;Retail
Display;Hospitality;Office;Restaurant;W

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1200.0
Mean Lumens (NOM) 1080.0
Nominal Initial Lumens per Watt (NOM)
Color Temperature (NOM) 3000.0 K
Color Rendering Index (CRI) 82.0
(NOM)

## **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 18.0
Voltage (NOM) 58.0
Lamp Current (NOM) 0.375 A
Current Crest Factor (MAX) 1.7

#### **DIMENSIONS**

Maximum Overall Length 9.000 in(228.6 mm) (MOL) (NOM)
Nominal Length (NOM) 9.000 in(228.6 mm)

### **PRODUCT INFORMATION**

Product Code 16649

Description F18BX/SPX30 10PK
ANSI Code 60901-IEC-2218-2
Standard Package BUNDLE

Standard Package GTIN 30043168166493 Standard Package Quantity 40

Standard Package Quantity 40
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 40

Package

UPC 043168166492

### NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.