




Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 16940**16940 – F18BX/SPX41 10PK**

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse


 High Color Rendering
Energy Savings
**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Wattage	18
Voltage	58
Rated Life	10000 hrs
Starting Temperature (MIN)	-4 °C (25 °F)
LEED-EB MR Credit	926 picograms Hg per mean lumen hour
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	1200
Mean Lumens	1080
Nominal Initial Lumens per Watt	66
Color Temperature	4100 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Lamp Current	0.375 A
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	10.5000 in (266.7 mm)
Nominal Length	9.000 in (228.6 mm)

PRODUCT INFORMATION

Product Code	16940
Description	F18BX/SPX41 10PK
ANSI Code	60901-IEC-2218-2
Standard Package	Master
Standard Package GTIN	10043168169407
Standard Package	40

ADDITIONAL RESOURCES[Catalogs](#)[Testimonials](#)[Disposal Policies & Recycling Information](#)

Quantity	
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168169400

CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life
- Life ratings for the F18BX preheat lamps are based on operating the lamp at 3 hrs per start on a preheat type circuit. Operation on rapid start and instant start ballasts is not recommended. Life ratings for all lamps are based on operating the lamp at 3 hrs per start on a rapid start type ballast. Life rating on a preheat or instant start ballast is 25% lower than other Rapid Start High Lumen Biax.

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2009