WORLDWIDE PARTNER	GE Lighting	Commercial Products & Solutions
SITE SEAR	CH > HOME	* PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS
Products > 10004		Where to Buy   FAQs   Contact Us   EliteNe
10004 – F4T5/CW GE Cool White Starcoat® T5		
GENERAL CHARACTERIST	ICS	
Lamp type	Linear Fluorescent - Straight Linear	ē-
Bulb	T5	
Base	Miniature Bi-Pin (G5)	
Wattage	4	
Voltage	29	
Rated Life	5000 hrs	Bulb Base
Bulb Material	Soda lime	
Starting Temperature (MIN)	10 °C (50 °F)	
LEED-EB MR Credit	12000 picograms Hg per mean lumen hour	
PHOTOMETRIC CHARACTE	RISTICS	View Larger
Initial Lumens	135	ADDITIONAL RESOURCES
Mean Lumens	100	
Nominal Initial Lumens per Watt	33	Catalogs <u>Testimonials</u> MSDS (Metazial Sefety Data Shorts)
Color Temperature	4100 K	<u>MSDS (Material Safety Data Sheets)</u> <u>Disposal Policies &amp; Recycling Information</u>
Color Rendering Index (CRI)	60	
ELECTRICAL CHARACTERISTICS		GRAPHS & CHARTS
Open Circuit Voltage (rapid start) (MAX)	165 V	Spectral Power Distribution
Open Circuit Voltage (after preheating) Max @ Temperature	210 V @ 10 °C	(\$2200 UNIT TERES TO A
Open Circuit Voltage (rapid start) Min @ Temperature	120 V @ 10 ℃	
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25	100
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5	So 000
Open Circuit Voltage (after preheating) Min @ Temperature	108 V @ 10 °C	300 360 400 450 500 650 600 650 700 750 Wavelength (nm)

## DIMENSIONS

Current Crest Factor (MAX) 1.7

Temperature

DIMENSIONS	
Maximum Overall Length (MOL)	5.9100 in (150.1 mm)
Nominal Length	6.000 in (152.4 mm)
Bulb Diameter (DIA)	0.625 in (15.8 mm)
Bulb Diameter (DIA) (MIN)	0.530 in (13.4 mm)

Lamp Mortality

Bulb Diameter (DIA) (MAX)	0.630 in (16.0 mm)	1009	6		CONTRACTOR OF		
Max Base Face to Base Face (A)	5.350 in (135.8 mm)	(%) 909 60 809	2	-		~	
Face to End of Opposing Pin (B) (MIN)	5.530 in (140.4 mm)	2 709	6 -	-	-		
Face to End of Opposing Pin (B) (MAX)	5.630 in (143.0 mm)	<b>3</b> 609 509	20-10 - I - I - I - I - I - I - I - I - I -				1
PRODUCT INFORMATION			0	1250 Ti	2500 me (hrs)	3750	5000
Product Code	10004						
Description	F4T5/CW						
ANSI Code	2001-1						
Standard Package	Case						
Standard Package GTIN	10043168100042						
Standard Package Quantity	24						
Sales Unit	Unit						
No Of Items Per Sales Unit	1						
No Of Items Per Standard Package	24						
UPC	043168100045						

See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright General Electric Company 1997-2009