

GE Lighting

### WORLDWIDE PARTNER

Commercial Products & Solutions



Where to Buy | FAQs | Contact Us | EliteNet

PRINT

<u>Products</u> > 46687

### 46687 - F21W/T5/841/ECO

GE Ecolux® Starcoat® T5

• Passes TCLP, which can lower disposal costs.

a product of

# ecomagination



### **GENERAL CHARACTERISTICS**

Lamp type	Linear Fluorescent - Straight Linear	
Bulb	T5	
Base	Miniature Bi-Pin (G5)	
Wattage	21	
Voltage	123	
Rated Life	30000 hrs	
Rated Life (rapid start) @ Time	30000 h @ 3 h 36000 h @ 12 h	
Bulb Material	Soda lime	
Starting Temperature (MIN)	-20 °C (-4 °F)	
LEED-EB MR Credit	78 picograms Hg per mean lumen hour	
Additional Info	TCLP compliant	

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	2100
Mean Lumens	1930
Nominal Initial Lumens per Watt	100
Color Temperature	4100 K
Color Rendering Index (CRI)	85
S/P Ratio (Scotopic/Photopic Ratio)	1.7


## **ELECTRICAL CHARACTERISTICS**

Open Circuit Voltage (rapid start) Min @ Temperature	340 V @ 10 ℃
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

## **DIMENSIONS**

Maximum Overall Length (MOL)	33.9800 in (863.0 mm)
Nominal Length	33.400 in (848.3 mm)






# ADDITIONAL RESOURCES

Catalogs Testimonials

<u>Disposal Policies & Recycling Information</u>


### **GRAPHS & CHARTS**

**Spectral Power Distribution** 



**Lamp Mortality** 


Bulb Diameter (DIA)	0.625 in (15.8 mm)
Bulb Diameter (DIA) (MAX)	0.670 in (17.0 mm)
Max Base Face to Base Face (A)	33.430 in (849.1 mm)
Face to End of Opposing Pin (B) (MIN)	33.610 in (853.6 mm)
Face to End of Opposing Pin (B) (MAX)	33.700 in (855.9 mm)



### PRODUCT INFORMATION

Product Code	46687
Description	F21W/T5/841/ECO
Standard Package	Case
Standard Package GTIN	10043168466872
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168466875





### **COMPATIBLE GE BALLASTS**

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
99655	GE228MVPS-A	1	99.0	1.16
99653	GE228MVPSH- A	1	99.0	1.24

## **A** CAUTIONS & WARNINGS

See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2009