



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 46708**46708 – F28W/T5/865/ECO**

GE Ecolux® Starcoat® T5




- Passes TCLP, which can lower disposal costs.

 a product of
ecomagination

High Color Rendering

**GENERAL CHARACTERISTICS**

Lamp type	Linear Fluorescent - Straight Linear
Bulb	T5
Base	Miniature Bi-Pin (G5)
Wattage	28
Voltage	167
Rated Life	30000 hrs
Rated Life (rapid start) @ Time	36000 h @ 12 h 30000 h @ 3 h
Bulb Material	Soda lime
Starting Temperature (MIN)	-20 °C (-4 °F)
LEED-EB MR Credit	61 picograms Hg per mean lumen hour
Additional Info	TCLP compliant

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)[Disposal Policies & Recycling Information](#)**PHOTOMETRIC CHARACTERISTICS**


Initial Lumens	2700
Mean Lumens	2480
Nominal Initial Lumens per Watt	96
Color Temperature	6500 K
Color Rendering Index (CRI)	85
S/P Ratio (Scotopic/Photopic Ratio)	2.2

ELECTRICAL CHARACTERISTICS


Open Circuit Voltage (rapid start) Min @ Temperature	425 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	45.8000 in (1163.3 mm)
Nominal Length	45.200 in (1148.0 mm)

GRAPHS & CHARTS**Spectral Power Distribution****Lamp Mortality**


Bulb Diameter (DIA)	0.625 in (15.8 mm)
Bulb Diameter (DIA) (MAX)	0.670 in (17.0 mm)
Max Base Face to Base Face (A)	45.240 in (1149.0 mm)
Face to End of Opposing Pin (B) (MIN)	45.420 in (1153.6 mm)
Face to End of Opposing Pin (B) (MAX)	45.520 in (1156.2 mm)



PRODUCT INFORMATION

Product Code	46708
Description	F28W/T5/865/ECO
Standard Package	Case
Standard Package GTIN	10043168467084
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168467087

Lumen Maintenance



COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
99655	GE228MVPS-A	1	99.0	1.09
99653	GE228MVPSH-A	1	99.0	1.21

YOU MIGHT ALSO BE INTERESTED IN...

For Energy
[GE Ecolux® Starcoat® T5](#)
 Product code: 71656

- Passes TCLP, which can lower disposal costs.

[COMPARE](#)

*Click on product for more specification details

CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

[Return To Top](#)