



WORLDWIDE PARTNER

Commercial Products & Solutions

SITE SEARCH > HOME * PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS

Where to Buy | FAQs | Contact Us | EliteNet

Products > 12956

12956 - F13DBXT4/SPX30

GE Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

₽RINT

This product is no longer manufactured. Remaining stock will be sold.



GENERAL CHARACTERISTICS				
Lamp type	Compact Fluorescent - Plug-In			
Bulb	T4			
Base	G24d-1			
Wattage	13			
Voltage	91			
Rated Life	10000 hrs			
Starting Temperature (MIN)	-15			
Cathode Resistance	10.500 Ohm			
LEED-EB MR Credit	530 picograms Hg per mean lumen hour			
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse			

PHOTOMETRIC	CHARACTERISTICS

900
755
69
3000 K
82


ELECTRICAL CHARACTERISTICS

Open Circuit Voltage Across Starter (MIN)	198 V
Lamp Current	0.175 A
Current Crest Factor (MAX)	1.7
Supply Current Frequency	60 Hz

DIMENSIONS

Maximum Overall Length (MOL)	5.2400
Nominal Length	5.300
Base Face to Top of Lamp	4.370





View Larger

ADDITIONAL RESOURCES

<u>Catalogs</u> <u>Testimonials</u>

Disposal Policies & Recycling Information

PRODUCT INFORMATION

12956
F13DBXT4/SPX30
60901-IEC-0513-1
BUNDLE
30043168129566
50
Unit
1
50
043168129565

COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
87533	GEM1CF13PH120	1	50.0	0.9
87655	GEM2CF13PH277	2	95.0	0.9

A CAUTIONS & WARNINGS

See list of cautions & warnings.

NOTES

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use Copyright General Electric Company 1997-2009