



GE
Lighting

Commercial Products & Solutions

[SITE SEARCH](#)

▶ [HOME](#)

▼ [PRODUCTS](#)

▶ [EDUCATION / RESOURCES](#)

▶ [LIGHTING APPLICATIONS](#)

[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)

[Products](#) > [Sealed Beam](#) > [Military](#) > 24833

24833 – 4572


GE PAR46 - Military

[Print this Page](#)

[Convert to PDF](#)

GENERAL CHARACTERISTICS

Lamp type	Sealed Beam - PAR
Bulb	PAR46
Base	Screw Terminals
Filament	CC-6
Product Technology	Incandescent
Wattage	150
Voltage	28
Rated Life	300 hrs
Primary Application	Military



Bulb



Base



Filament



[View Larger](#)

PHOTOMETRIC CHARACTERISTICS

Beam Spread - Horizontal	55° - 10 %
Beam Spread - Vertical	55° - 10 %
Max. Beam Candlepower (MBCP) (MAX)	4500

DIMENSIONS

Maximum Overall Length (MOL)	3.7500 in (95.2 mm)
Bulb Diameter (DIA)	5.750 in (146.0 mm)

PRODUCT INFORMATION

Product Code	24833
Description	4572
ANSI Code	4572
Standard Package	Case
Standard Package GTIN	00043168248334
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168962407

ADDITIONAL RESOURCES

[Catalogs](#)

[Disposal Policies & Recycling Information](#)

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Careers](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright 2010 General Electric Company