



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > 15831**15831 – FLE15HT3/2/827**

GE Soft White Spiral® T3 - Facilities; Retail Display; Hospitality; Office; Restaurant



- Up to 75% energy savings One piece unit screws directly into incandescent sockets T3 Spirals® lamps provide economical solution with small overall size

 a product of
ecomagination™


- High Color Rendering
- cUL Listed
- Energy Savings
- UL Listed


**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Self-Ballasted
Bulb	T3
Base	Medium Screw (E26)
ENERGY STAR® Qualified	Yes
Wattage	15
Voltage	120
Rated Life	8000 hrs
Starting Temperature (MIN)	-15 °C (5 °F)
Total Harmonic Distortion (THD)	145 %
Picograms of Mercury	572 picograms
Primary Application	Standard; Facilities; Retail Display; Hospitality; Office; Restaurant

Bulb



Base



Package

[View Larger](#)**ADDITIONAL RESOURCES**[Catalogs](#)[Testimonials](#)**Brochures**

Product Brochures

- [Compact Fluorescent Lamps](#)
- [GE Consumer & Industrial ENERGY STAR® Program](#)

[Disposal Policies & Recycling Information](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	950
Mean Lumens	765
Nominal Initial Lumens per Watt	63
Color Temperature	2700 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Input Voltage	120 V
Input Current	0.2300 A
Power Factor	0.6

DIMENSIONS

Maximum Overall Length (MOL)	4.8000 in (121.9 mm)
Nominal Length	4.800 in (121.9 mm)

PRODUCT INFORMATION

Product Code	15831
Description	FLE15HT3/2/827
Standard Package	Case
Standard Package GTIN	10043168158319
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168158312

 CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

NOTES

- Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2008