WORLDWIDE PARTNER	Lighting	Commercial Products & Solutions
SITE SEARC	CH > HOME *	PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS
		Where to Buy   FAQs   Contact Us   EliteNe
Products > 23077		
<b>23077 – F60T12/D/HO</b> 1 GE Daylight T12	15PK	
High Color Rendering		Bulb Base
GENERAL CHARACTERISTICS		
Lamp type	Linear Fluorescent - Straight Linear	
Bulb	T12	View Larger
Base	Recessed Double Contact (R17d)	ADDITIONAL RESOURCES
Wattage	75	Catalogs
Voltage	98	Testimonials
Rated Life	12000 hrs	Brochures
Bulb Material	Soda lime	Application/Segment Brochures
Starting Temperature (MIN)	-29 ℃ (-20 F)	<u>Canopy Lighting</u> <u>MSDS (Material Safety Data Sheets)</u>
Picograms of Mercury	1958 picograms	Disposal Policies & Recycling Information
PHOTOMETRIC CHARACTE	RISTICS	GRAPHS & CHARTS
nitial Lumens	4400	Spectral Power Distribution
Mean Lumens	3830	
Nominal Initial Lumens per Watt	58	
Nominal Initial Lumens per Watt Color Temperature	58 6500 K	
Nominal Initial Lumens per Watt	58	
Nominal Initial Lumens per Watt Color Temperature	58 6500 K 75	300 (steam), 100 100 100 100 100 100 100 100 100 10
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI)	58 6500 K 75	300 (steam), 100 100 100 100 100 100 100 100 100 10
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERI Open Circuit Voltage (rapid	58 6500 K 75 STICS 325 V @ 10 °C	Brdiant Power (JWI/10/mrl
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERIS Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio -	58 6500 K 75 <b>STICS</b> 325 V @ 10 °C 365 V @ -29 °C	100 model with the second seco
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERIS Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio -	58 6500 K 75 STICS 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25	
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERI Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX)	58 6500 K 75 STICS 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5	solution of the second
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERI Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX) DIMENSIONS	58         6500 K         75         STICS         325 V @ 10 ℃         365 V @ -29 ℃         4.25         6.5         1.7	solution of the second
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERIS Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX) DIMENSIONS Maximum Overall Length MOL)	58 6500 K 75 <b>STICS</b> 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5 1.7 57.9100 in (1470.9 mm)	solution of the second
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERIS Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX) DIMENSIONS Maximum Overall Length MOL) Minimum Overall Length	58 6500 K 75 STICS 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5 1.7 57.9100 in (1470.9 mm) 57.7200 in (1466.0 mm)	solution of the second
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERIS Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX) DIMENSIONS Maximum Overall Length MOL) Minimum Overall Length	58 6500 K 75 STICS 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5 1.7 57.9100 in (1470.9 mm) 57.7200 in (1466.0 mm) 60.000 in (1524 mm)	$\frac{1}{90} \frac{1}{90} \frac{1}{90} \frac{1}{90\%} \frac{1}{90$
Jominal Initial Lumens per Vatt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERI Open Circuit Voltage (rapid ttart) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX) DIMENSIONS Maximum Overall Length MOL) Minimum Overall Length Jominal Length Bulb Diameter (DIA)	58 6500 K 75 STICS 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5 1.7 57.9100 in (1470.9 mm) 57.7200 in (1466.0 mm)	$\frac{1}{90} \frac{1}{90} \frac$
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERI Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX) Current Crest Factor (MAX) DIMENSIONS Maximum Overall Length MOL) Minimum Overall Length Nominal Length Bulb Diameter (DIA) (MIN)	58 6500 K 75 STICS 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5 1.7 57.9100 in (1470.9 mm) 57.7200 in (1466.0 mm) 60.000 in (1524 mm)	
Nominal Initial Lumens per Watt Color Temperature Color Rendering Index (CRI) ELECTRICAL CHARACTERI Open Circuit Voltage (rapid start) Min @ Temperature Cathode Resistance Ratio - Rh/Rc (MIN) Cathode Resistance Ratio - Rh/Rc (MAX)	58 6500 K 75 <b>STICS</b> 325 V @ 10 ℃ 365 V @ -29 ℃ 4.25 6.5 1.7 57.9100 in (1470.9 mm) 57.7200 in (1466.0 mm) 60.000 in (1524 mm) 1.500 in (38.1 mm)	$\frac{1}{90} \frac{1}{90} \frac$

http://genet.gelighting.com/LightProducts/Dispatcher?REQUEST=COMMERCIALSPEC... 6/17/2008

Product Code	23077
Description	F60T12/D/HO 15PK
ANSI Code	1014-1
Standard Package	Case
Standard Package GTIN	10043168230770
Standard Package Quantity	15
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	15
UPC	043168230773

## **A** CAUTIONS & WARNINGS

See list of cautions & warnings.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright General Electric Company 1997-2008