


## 17986 - 100PAR/H/FL25

# GE Floodlight PAR38

- Designed with a unique all-weather construction, they withstand harsh weather conditions better than regular hulbs.
- Uses Halogen technology for a brighter, crisper light
- GE's Floodlights cast a wider beam that adds drama to driveways and yards.

# Photo Not Available

Energy











## **CAUTIONS & WARNINGS**

#### Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Burn
- Allow lamp to cool before handling.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.

#### **GENERAL CHARACTERISTICS**

Lamp Type Halogen - PAR

Bulb PAR38

Base Medium Skirt (E26/50x39)

Filament CC-8
Rated Life 2000.0 hrs
Primary Application Yard Stake

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens 1500.0 Center Beam Candlepower 5000.0

(CBCP)

Color Temperature 2900.0 K Nominal Initial Lumens per Watt 15

# **ELECTRICAL CHARACTERISTICS**

Wattage 100.0 Voltage 120.0

## **DIMENSIONS**

Maximum Overall Length 5.3130 in(135.0 mm)

(MOL)

Bulb Diameter (DIA) 4.750 in(120.6 mm)

## **PRODUCT INFORMATION**

Product Code 17986

Description 100PAR/H/FL25

Standard Package Case

Standard Package GTIN 10043168179864

Standard Package Quantity 6
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 6

Package

UPC 043168179867