


42067 – CMH39PAR30L/FL25

GE ConstantColor® PulseArc® CMH® Ceramic Metal Halide PAR30L

GENERAL CHARACTERISTICS

Lamp type	High Intensity Discharge - Ceramic Metal Halide
Bulb	PAR30L
Base	Medium Screw (E26)
Wattage	39
Rated Life	10000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Additional Info	Ballast thermal protection, UV control

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	2400
Nominal Initial Lumens per Watt	61
Beam Spread	25 °
Center Beam Candlepower (CBCP)	11000
Color Temperature	3000 K
Color Rendering Index (CRI)	81

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Open Circuit Voltage (peak lead ballast) (MIN)	280 V
Open Circuit Voltage (RMS lag ballast) (MIN)	198 V
Warm Up Time to 90%	2 min
Warm Up Time to 90% (MAX)	2 min/3 min
Hot Restart Time to 90% (MIN)	10 min
Hot Restart Time to 90% (MAX)	15 min

DIMENSIONS

Maximum Overall Length (MOL)	4.7500 in (120.6 mm)
Nominal Length	4.600 in (116.8 mm)
Bulb Diameter (DIA)	3.813 in (96.8 mm)

PRODUCT INFORMATION

Product Code	42067
Description	CMH39PAR30L/FL25
ANSI Code	M130
Standard Package	Case
Standard Package GTIN	10043168420676
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales	1

ADDITIONAL RESOURCES**Catalogs****Testimonials****Brochures**

Product Brochures

- [Ceramic Metal Halide](#)
- [Color](#)
- [HID Lamps](#)

Application/Segment Brochures

- [Contractor Lighting](#)
- [Hospitality Lighting](#)
- [Restaurant Lighting](#)

Sell Sheets

- [GE ConstantColor® CMH® Lamps](#)

IES/Photometric Download**MSDS (Material Safety Data Sheets)****Disposal Policies & Recycling Information**

Unit

No Of Items Per Standard Package	6
----------------------------------	---

UPC	043168420679
-----	--------------

COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
87501	GEMH39-MSF-120	1	99.0	1.0

⚠ CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information:

<http://www.fda.gov/cdrh/radhealth/products/urburns.html>

[See list of cautions & warnings.](#)

NOTES

- Rated life based on 11 hours per start
- Use electronic ballast, peak lead ballast, or system which can shut itself off if ballast overheating occurs