




Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 20016**20016 – CMH70TU/830/G12**

GE ConstantColor® PulseArc® CMH® Ceramic Metal Halide T6


 a product of
ecomagination
[View Larger](#)**GENERAL CHARACTERISTICS**

Lamp type	High Intensity Discharge - Ceramic Metal Halide
Bulb	T6
Base	Bi-Pin (G12)
Wattage	70
Rated Life	15000 hrs
Bulb Material	Quartz
Lamp Enclosure Type (LET)	Enclosed fixtures only
LEED-EB MR Credit	65 picograms Hg per mean lumen hour
Additional Info	UV control

ADDITIONAL RESOURCES**Catalogs****Testimonials****Sell Sheets**

- [ConstantColor® CMH® Single-Ended G12 Lamps - OEM Data Sheet](#)
- [ConstantColor® CMH® Single-Ended G12 Lamps](#)

MSDS (Material Safety Data Sheets)**Disposal Policies & Recycling Information****PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	6200
Mean Lumens	4700
Nominal Initial Lumens per Watt	88
Color Temperature	3000 K
Color Rendering Index (CRI)	83

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Warm Up Time to 90% (MAX)	2 min/3 min
Hot Restart Time to 90% (MIN)	10 min
Hot Restart Time to 90% (MAX)	15 min

DIMENSIONS

Maximum Overall Length (MOL)	3.5600 in (90.4 mm)
Light Center Length (LCL)	2.180 in (55.3 mm)

PRODUCT INFORMATION

Product Code	20016
Description	CMH70TU/830/G12