



Commercial Products & Solutions


 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 81514**81514 – FLE29HLX/2XL/827**

GE Soft White Spiral® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant


 a product of
ecomagination

 High Color Rendering
 Energy Savings
 UL Listed

Base

[View Larger](#)**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Self-Ballasted
Bulb	T4
Base	Medium Screw (E26)
ENERGY STAR® Qualified	Yes
Wattage	29
Equivalent Wattage	100 W
Rated Life	12000 hrs
Starting Temperature (MIN)	-15 °C (5 °F)
Picograms of Mercury	133 picograms
Primary Application	Standard; Facilities; Retail Display; Hospitality; Office; Restaurant

ADDITIONAL RESOURCES**Catalogs****Testimonials****Brochures**

Product Brochures

- [GE Consumer & Industrial ENERGY STAR® Program](#)

Disposal Policies & Recycling Information**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	2200
Nominal Initial Lumens per Watt	75
Color Temperature	2700 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Input Voltage	120 V
---------------	-------

DIMENSIONS

Maximum Overall Length (MOL)	6.3000 in (160.0 mm)
Nominal Length	6.300 in (160.0 mm)

PRODUCT INFORMATION

Product Code	81514
Description	FLE29HLX/2XL/827
Standard Package	Case
Standard Package GTIN	10043168815144

Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168815147

▲ CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2008