

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	Base Type	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila-ment Type	LCL (mm)	MOL (mm)	Burning Position	Bulb Finish	Fig. No.
<b>Table 8: Halogen, Single-Ended, G9.5 Medium 2-Pin (9.5mm apart) (continued)</b>																		
750	T-6	<b>GLD-0750T6/4CL</b>	62	GLD	—	<b>92771</b>	24	G9.5	115	3200	300	19000	C-13D	60	105	Any		9
		<b>GLE-0750T6/4CL</b>	62	GLE	—	<b>92773</b>	24	G9.5	115	3050	1500	17400	C-13D	60	105	Any		9
	T-7	<b>BWM-0750T7/4CL/TP</b>	1, 62	BWM	—	<b>39680</b>	6	G9.5	120	3200	200	21000	C-13D	60	114	BDTH		9
800	T-6	<b>HX800</b>	62		HX800	<b>39753</b>	24	G9.5	230	3200	250	20000	C-13D	60	105	Any		9
		<b>HX800</b>	62		HX800	<b>39754</b>	24	G9.5	240	3200	250	20000	C-13D	60	105	Any		9
1000	T-6	<b>FEL-01000/4CL</b>	62,22	FEL	CP77	<b>39769</b>	24	G9.5	120	3200	300	27500	CC-8	60	105	Any		8
		<b>FEP-01MT6/4CL</b>	62	FEP	CP77	<b>39738</b>	24	G9.5	230	3200	300	25000	CC-8	60	105	Any		8
		<b>FEP-01MT6/4CL</b>	62	FEP	CP77	<b>39736</b>	24	G9.5	240	3200	300	25000	CC-8	60	105	Any		8
	T-7	<b>BWN-01000T7/4CL/TP</b>	62,1	BWN	—	<b>39792</b>	24	G9.5	120	3200	250	28500	C-13D	60	114	BDTH		9
<b>Table 9: Halogen, Single-Ended, G9.5/Heat Sink (Metal 2-Pin)</b>																		
375	T-6	<b>HPL375/C</b>	18, 62			<b>17608</b>	12	G9.5/HS	115	3250	300	10540	4-C8	60	106	Any		10
		<b>HPL375/LL</b>	18, 62			<b>18189</b>	12	G9.5/HS	115	3050	1000	8000	4-C8	60	106	Any		10
550	T-6	<b>HPL550/C 77V</b>	18, 62			<b>17607</b>	12	G9.5/HS	77	3250	300	16170	4-C8	60	106	Any		10