

GE Lighting

Halogen - MR MR16

2-Pin (GU5.3)

C-6

35

12

5000 hrs Covered glass

#### WORLDWIDE PARTNER

Commercial Products & Solutions

SITE SEARCH > HOME \*\* PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS

Where to Buy | FAQs | Contact Us | EliteNet

₽RINT

Products > Halogen > MR > MR16 > 20864

### 20864 - Q35MR16/C/CG12

**GENERAL CHARACTERISTICS** 

GE ConstantColor® Precise™ MR16

• UV protection

Lamp type

Filament Wattage

Voltage

Rated Life

Bulb Base









View Larger

# PHOTOMETRIC CHARACTERISTICS

Lamp Enclosure Type (LET)

Center Beam Candlepower (CBCP)	7500
Color Temperature	3000 K
Nominal Initial Lumens per Watt	214

# **ELECTRICAL CHARACTERISTICS**

Burn Position	Universal burning position
DIMENSIONS	
Maximum Overall Length (MOL)	1.8750 in (47.6 mm)
Bulb Diameter (DIA)	2.000 in (50.8 mm)

# PRODUCT INFORMATION

Product Code	20864
Description	Q35MR16/C/CG12
ANSI Code	FRB
Standard Package	BUNDLE
Standard Package GTIN	00043168208642
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168994170

**A** CAUTIONS & WARNINGS

See list of cautions & warnings.

# ADDITIONAL RESOURCES

# Catalogs

#### **Testimonials**

#### **Brochures**

**Product Brochures** 

- Color
- XL Brochure

Application/Segment Brochures

- Contractor Lighting
- Healthcare Lighting
- Office Lighting

#### **Sell Sheets**

GE ConstantColor® Precise™ MR16 Lamps

**IES/Photometric Download** 

MSDS (Material Safety Data Sheets)

**Disposal Policies & Recycling Information** 

20864 - Specifications - GE Commercial Lighting Products	Page 2 of 2
	Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2008