



GE  
Lighting

Commercial Products & Solutions

[SITE SEARCH](#)

▶ [HOME](#)

▼ [PRODUCTS](#)

▶ [EDUCATION / RESOURCES](#)

▶ [LIGHTING APPLICATIONS](#)

[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)

[Products](#) > [Sealed Beam](#) > [PAR](#) > [PAR56](#) > 20836

## 20836 – 300PAR56/MFL


GE PAR56 - Medium Flood

[Print this Page](#)

[Convert to PDF](#)

### GENERAL CHARACTERISTICS

Lamp type	Sealed Beam - PAR
Bulb	PAR56
Base	Mogul End Prong (GX16d)
Filament	CC-13
Product Technology	Incandescent
Wattage	300
Voltage	120
Rated Life	2000 hrs
Primary Application	Medium Flood



Bulb



Base



Filament



[View Larger](#)

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	3840
Beam Spread - Horizontal	34° - 10 %, 23° - 50 %
Beam Spread - Vertical	19° - 10 %, 11° - 50 %
Center Beam Candlepower (CBCP)	24000
Color Temperature	2750 K
Nominal Initial Lumens per Watt	12

### ADDITIONAL RESOURCES

[Catalogs](#)

[IES/Photometric Download](#)

[Disposal Policies & Recycling Information](#)

### DIMENSIONS

Maximum Overall Length (MOL)	5.0000 in (127 mm)
Bulb Diameter (DIA)	7.000 in (177.8 mm)

### PRODUCT INFORMATION

Product Code	20836
Description	300PAR56/MFL
Standard Package	Case
Standard Package GTIN	10043168208366
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168208369

### CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

### NOTES

- For use with heat-resistant connector supported by bulb

rim or metal shell of base.

- Lamp is made of heat resistant glass (HRG).
- 

[Return To Top](#)

---

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)  
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Careers](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright 2010 General Electric Company