



GE Consumer & Industrial
Lighting

Print Close

Lighting Specification Bulletin

E-Z Lux High Presure Sodium Lamps (Mercury Retrofit) Product Code: 49943 Description: LUH150/EZ		Product Image																																																		
Specification: Firm Name : Job Name :																																																				
<table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Product Code</td> <td>49943 Reduced Wattage LSB Data Available</td> </tr> <tr> <td>Description</td> <td>LUH150/EZ</td> </tr> <tr> <td>Subcategory</td> <td>E-Z Lux High Presure Sodium Lamps (Mercury Retrofit)</td> </tr> <tr> <td colspan="2">Physical</td> </tr> <tr> <td>Bulb Type</td> <td>ED28</td> </tr> <tr> <td>Base Type</td> <td>Mog</td> </tr> <tr> <td>Max Overall Length (In.)</td> <td>9</td> </tr> <tr> <td>Max Overall Length (mm)</td> <td>229</td> </tr> <tr> <td>Nominal Length (In.)</td> <td>9.00</td> </tr> <tr> <td>Bulb Nominal Diameter (In.)</td> <td>3.5</td> </tr> <tr> <td colspan="2">Photometric</td> </tr> <tr> <td>Average Life in Hours</td> <td>13000</td> </tr> <tr> <td>Lumens (Initial)</td> <td>12500</td> </tr> <tr> <td>Lumens (Mean)</td> <td>12000</td> </tr> <tr> <td>Color Temperature (K)</td> <td>1900</td> </tr> <tr> <td>Warm Up Time (min.) to 90%</td> <td><15</td> </tr> <tr> <td>Effective Arc Length in inches</td> <td>1.8900</td> </tr> <tr> <td>Lighted Center Length (In.)</td> <td>5</td> </tr> <tr> <td colspan="2">Electrical</td> </tr> <tr> <td>Watts</td> <td>150</td> </tr> <tr> <td colspan="2">Luminaire</td> </tr> <tr> <td>Operating Position Code</td> <td>U</td> </tr> <tr> <td colspan="2">Ballast-related information</td> </tr> <tr> <td>Minimum Ballast Open Circuit Voltage - RMS - Lag Ballast (Ballast A/B/C)</td> <td>225</td> </tr> </table>		General		Product Code	49943 Reduced Wattage LSB Data Available	Description	LUH150/EZ	Subcategory	E-Z Lux High Presure Sodium Lamps (Mercury Retrofit)	Physical		Bulb Type	ED28	Base Type	Mog	Max Overall Length (In.)	9	Max Overall Length (mm)	229	Nominal Length (In.)	9.00	Bulb Nominal Diameter (In.)	3.5	Photometric		Average Life in Hours	13000	Lumens (Initial)	12500	Lumens (Mean)	12000	Color Temperature (K)	1900	Warm Up Time (min.) to 90%	<15	Effective Arc Length in inches	1.8900	Lighted Center Length (In.)	5	Electrical		Watts	150	Luminaire		Operating Position Code	U	Ballast-related information		Minimum Ballast Open Circuit Voltage - RMS - Lag Ballast (Ballast A/B/C)	225	Dimensionalized Line Art - Small Product Image Dimensionalized Line Art - Large Product Image
General																																																				
Product Code	49943 Reduced Wattage LSB Data Available																																																			
Description	LUH150/EZ																																																			
Subcategory	E-Z Lux High Presure Sodium Lamps (Mercury Retrofit)																																																			
Physical																																																				
Bulb Type	ED28																																																			
Base Type	Mog																																																			
Max Overall Length (In.)	9																																																			
Max Overall Length (mm)	229																																																			
Nominal Length (In.)	9.00																																																			
Bulb Nominal Diameter (In.)	3.5																																																			
Photometric																																																				
Average Life in Hours	13000																																																			
Lumens (Initial)	12500																																																			
Lumens (Mean)	12000																																																			
Color Temperature (K)	1900																																																			
Warm Up Time (min.) to 90%	<15																																																			
Effective Arc Length in inches	1.8900																																																			
Lighted Center Length (In.)	5																																																			
Electrical																																																				
Watts	150																																																			
Luminaire																																																				
Operating Position Code	U																																																			
Ballast-related information																																																				
Minimum Ballast Open Circuit Voltage - RMS - Lag Ballast (Ballast A/B/C)	225																																																			

Minimum Ballast Open Circuit Voltage - Peak Lag Ballast (Ballast A/B/C)	318
Miscellaneous	
ANSI Ballast Type	H39
Additional Information	Clear, Energy-saving Retrofit for 175W Mercury
Footnotes	Use only with the following types of H39 175-watt mercury ballasts: high-reactance lag-type autotransformers or 240-volt and 277-volt reactors. Do not use with CW (lead-type) or CWA ballasts.

All values are design values or typical values when measured under laboratory conditions. Information provided is subject to change without notice. Where applicable, values are based on guidelines published in ANSI. For more information see Terms and Conditions in the link below.

Reduced Wattage Reduced Wattage LSB Data Available LSB Data Available